

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

VETRI

TECHNICAL CHARACTERISTICS

Available Formats:	24X24, 12X24, 8X24, 4X12		
Style Description:	Glass Look	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Shiny smooth plain color	Number of Faces/Screens:	1
Thickness in mm:	9mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy Polished
Rectified:	Yes	Recommended Grout Joint:	2 mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	Complaint
Frost Resistant:	Yes	Thermal Shock Resistance:	Complaint
PEI/Abrasion Resistance:	IV+	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Compliant		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.56	Pieces per Carton:	7
SqFt per Pallet:	542.40	Pounds per Carton:	
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".