

Product Specifications  
Anto-Fatigue Static Dissipative Matting



**Description**

S1506 is a static dissipative Vinyl matting ideal for areas that requires employees to work on standing position for long hours. It helps to reduce the fatigue, while providing a static free work surface to discharge static build up. Standard roll sizes are 3' x 60' & 4' x 60'. This product meets and exceeds ANSI/ESD S20.20-2014.

## Specifications<sup>(1)</sup>

Colors	Gray, Brown
Emboss Pattern	Pebble
Thickness	0.375" +/-10%
Weight	86 oz/square yard
Tensile Strength	70 ld/square inch, ASDM-D-412
Elongation @ Break	60%, ASDM-D-412
Tear	15 lb/in, ASTM D1004
Durameter (Shore 00)	60+/-5, ASDM-D-2240-75
Resistance from Surface To Groundable Point RTG	10 <sup>9</sup> -10 <sup>10</sup> ohms, EOS/ESD-S4
Resistance between Two Points on Surface, RTT	10 <sup>9</sup> -10 <sup>10</sup> ohms, EOS/ESD-S4
Charge Decay Time 5,000V to 50V	<2 Seconds, FTMS 101C Method 4046C
Suggested Service Temperature <sup>(2)</sup>	-20° F to +160° F

(1) Specifications are subjected to change any time for a variety of reasons. If you have questions, please call for the latest update.

(2) This suggested range represents the general temperature range for most flexible vinyl products.

### Standard Roll Sizes

- 36" x 60'
- 48" x 60'