



COMPACT, ENERGY EFFICIENT SOLENOID VALVES

Components For Automation, Inc.

4525 E. Industrial St.

Unit 4C

Simi Valley, CA 93063



1/8" NPT & 1/4" NPT Direct Acting



- 2- & 3-way Normally Closed and Open
- Noryl, Stainless Steel & Brass bodies

Solenoid Valve Manifolds



- 1/8", 1/4" & 3/8" NPT Inlets and Outlets
- Brass, Stainless Steel & Composite materials

3/8" to 2" NPT Piloted Diaphragm



- Nylon bodies; 2-way NC and NO
- 3/8", 1/2", 3/4", 1", 1-1/2", 2" NPT ports



- Nylon bodies; 2-way NC and NO
- 3/8", 1/2", 3/4" NPT ports

Metallic Bodies

- 3/8", 1/2", 3/4", 1" NPT ports



Components For Automation, Inc.

4525 E. Industrial St.
Unit 4C
Simi Valley, CA 93063



Our versatile C9 and C4 operators can be mounted on a wide variety of bodies, manifolds and custom assemblies.

C9 Compact Operator 22mm Direct Acting

- Rated to 50 million cycles
- 2- and 3-way
- Vacuum to 580 psi
- Cv to 0.30
- Orifices to 5/23"
- Brass, Aluminum, Stainless Steel, Composite bodies
- Buna, Kalrez, Viton, EPDM, Teflon seals
- Uses DIN 43650 Form B Connector
- Standard industrial/commercial voltages

C4 High Performance Operator 32mm Direct Acting

- Rated to 20 million cycles
- 2- and 3-way
- Vacuum to 2030 psi
- Cv to 1.0
- Orifice to 5/16"
- Brass, Aluminum, Stainless Steel, Composite bodies
- Buna, Kalrez, Viton, EPDM, Teflon seals
- Uses DIN 43650 Form A Connector
- Standard commercial/industrial voltages

The DIN Connector System

Our solenoid valve operators are available with coils with leads or with DIN international standard tab coils, an international standard.

DIN 43650 Connectors

- NEMA 4
- Strain Relief and ½" Conduit
- Available with any length cable
- With 6' cord and 120vac wall plug
- LED Power Indicator
- Surge Suppression
- DC Rectified
- Digital or Analog On/Off Timers

Solenoid Valve Options

- Direct Mount
- Angle Body
- Stainless Steel trim
- Metering
- Manual Override
- Inert Plating
- Oxygen Service Cleaned
- Submersible
- SAE, British Pipe Thread and other threads

Can't find what you need in a catalog?

We'll integrate our time-tested solenoid valve operators in a custom design to meet your application requirements. Contact your Region Office to learn more:

- chuck.stevens@cfa-inc.com
- tel 724-772-8900