

Lightning Rod Rules

North Central Arkansas Speedway, LLC

Bodies: Any Factory OEM Small to Mid-size Front Wheel Drive Production car- 4 cylinder or v6 motors only, NO CONVERTIBLE'S, sunroofs and t- tops MUST be closed up. Any rear wheel drive 4 CYLINDER mid or compact car will be allowed, MUST BE FACTORY STOCK WITH NO. **NO 4 or All wheel drive vehicles allowed!**

NO WEIGHT MAY BE ADDED TO CARS, PERIOD, TO ANY CAR FWD or RWD.

NO gutting except for removal of all flammables and glass, only gutting of car for allowance for a minimum 4-point roll cage with 4 door bars in driver's door and minimum of 18-ga door plate welded to door bars, tubing diameter must not be any smaller than 1 1/2" .095 thickness (1.75" x 0.095 preferred). **ROLLCAGE MUST BE WELDED TO DOUBLER PLATES BETWEEN CAGE AND BODY** (Doubler plates must consist of 4" x 6" x 3/16" thickness steel and welded to floor-pan or frame) **MUST HAVE COMPLETE FIREWALL FRONT AND REAR**

Engine: Motors must be **FACTORY STOCK** as they came from factory, **NO TURBOS, NO BLOWERS, NO PERFORMANCE CHIPS, NO REPROGRAMING, NO ALTERATIONS PERIOD.** OEM size throttle body for that motor and trans, **NO MSD** anywhere, single tip spark plugs only. OEM airbox and filters required. **MUST HAVE OEM COMPUTER HOOK UP TO HOOK SCANNER TO.**

Front wheel drive cars must be complete OEM body and frames as they came from factory stock suspension, bumper to bumper factory stock OEM, legal to drive on street other than installation of roll cage and removal of glass, interior. **NO RACING SPRINGS, SHOCKS OR RACING SUSPENSION OMPONENTS PERIOD.**

All doors and bumpers must be bolted or welded as to keep them with car, front and rear bumpers must stay under original bumper covers, if original bumper is damaged beyond repair a lightweight tubing bumper may be installed but must remain under OEM or OEM style bumper cover with no open ended pipes or turn downs on end of pipes Driver safety is a must, must have window net, racing seat belts, racing aluminum seat, fire extinguisher (dry chemical only), driver must wear racing suit, gloves, neck brace or HANS system, helmet must be Snell 90 or SA 95 rating or better.

Fuel: Gasoline only, **IF STOCK FUEL TANK IS USED MUST EITHER BE MOVED INTO TRUNK AREA OR MUST HAVE BARS INSTALLED TO PROTECT IT IN STOCK LOCATION, MUST HAVE FIREWALL BETWEEN DRIVER AND TANK**

Batteries must be moved into safe location and be inside a battery box and securely fastened to car

Wheels & Tires: NO OFF ROAD, MUD TIRES, OR RACING TIRES. OEM street tires only. Must be same size all the way around car **NO GROOVING OR SIPING.**

CAR Numbers must be clearly marked, 20" in height, and must be clearly legible and in a contrasting color to the main colors of the car.

CARS MUST REMAIN FACTORY STOCK, AS YOU WOULD BUY AND DRIVE ON STREET.