

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

ALABASTRINO

## TECHNICAL CHARACTERISTICS

Available Formats:	17x17, 12x12, 8x12 Wall, 2x2 Mosaic 12x12 Sheet, 3x12 Floor Bullnose, 2x8 Wall Bullnose		
Style Description:		Glaze Application Method:	Rotocolor
Visual Characteristics:	Honed Stone	Number of Faces/Screens:	4
Thickness in mm:	N/A	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Ceramic (>.5%)
Application:	Residential	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	Minimum 3/16th

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	>.5%	Static COF:	Wet: 0.55 Dry: 0.58
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	5	Breaking Strength:	N/A
Frost Resistant:	No	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	N/A		

## PACKING INFORMATION - 17x17 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	22.06	Pieces per Carton:	11
SqFt per Pallet:	1058.88	Pounds per Carton:	76.77
Boxes per Pallet:	48	SqFt per Container:	N/A
Pallets per Container:	N/A		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".