

PHONE 214-477-134 FAX972-317-6889 WWW.EICGROUPUSA.COM





Vacuum System Specifications

The Performance of One S-2700 Unit

Motor: 8.4" Voltage: 120 A.C.

Shipping Weight - Power Unit (Approx.): 55.0 lbs

Max Amperage (Approx.): 13.8 amps

Electrical Service to Unit: 120 volt; 20 amp receptical

Pump: Tangential 2-Stage By-pass

Airflow @ 2" Opening (Approx.): 142 C.F.M. Sealed Vacuum (Approx.): 147" H2O

Vacuum Pump Housing: Diameter (Approx): 13-5/8" Height (Approx.): 15-3/4"

Primary Powder Canister - DC-1240:

Filtration: Cyclonic primary, standpipe secondary,

with convenient lift off inspection lid.

Diameter: 16-1/8" Height: 40-1/4"

Powder Canister Capacity (Approx.): 38 Qts.

Shipping Weight - Powder Canister (Approx.): 23.0 lbs.

Secondary Powder Canister - DC-500:

Filtration: Disposable Paper Bag Inlet and Outlet Connections: 2"

Diameter: 13-5/8" Height: 25-3/4"

Capacity (Approx.): 27 Qts.

Shipping Weight (Approx.): 10.0 lbs. Replacement Filter: HPB-2H

This unit is 1,500 hours & DB rating of 60 db. 8.4" 2-stage Tangential By Pass motor

Constructed from Galvannealed steel & powder coated finish.

Notes: Ambient Temperature must be below 100° F.

If unit over heats, you must unplug and replug the unit in to get it to start again. **Unit must be kept well ventilated.**

(DO NOT MOUNT OVER 8' HIGH IN WARM AREAS.)

NOTE: ALL METAL TUBING AND FITTINGS MUST BE GROUNDED.



www.eicgroupusa.com

Central Vacuum System Assembly Kit

Powder Vac Includes:

| 1 | S-2700 | POWER UNIT |
|------|-------------------|--------------------------------------|
| 1 | DC-500 | HEPA BAG FILTERED DIRT CANISTER |
| 1 | DC-300 DC-1240 | 14" CYCLONIC DIRT CANISTER |
| 1 | 12' SF-207 | |
| 1 5 | | |
| 15 | SF-213 | 2" STEEL 90 DEGREE ELL |
| 2 | SF-216 | 2" STEEL 45 DEGREE ELL |
| 1 | SF-215 | 2" STEEL 90 DEGREE TY |
| 10 | SF-202 | 2" STEEL COUPLING |
| 1 | PF-200SW | SQUARE MUFFLER |
| 19 | PF-2051'W | TUBING STRAP |
| 110' | 2VM1000UL | REMOTE CONTROL WIRE |
| 59 | SS-200 | HEAT SHRINK SLEEVE |
| 2 | UA-221X | 1-1/2" UTILTIY VALVE W/ MICRO SWITCH |
| 1 | CH-225 | 1-1/2" X 30' CONDUCTIVE HOSE |
| 1 | IWA-24 | 48" DOUBLE CURVED INDUSTRIAL WAND |
| 1 | IFB-635 | 14" METAL HEAVY DUTY FLOOR BRUSH |
| 1 | IW-224 | METAL HEAVY HANDY TOOL |
| 1 | IW-221-2 | BRUSH FOR IW-224 |
| 1 | ICT-624A-1 | 24" LONG METAL CREVICE TOOL |
| 1 | H-331 | HOSE HANGER |
| 1 | CB-180 | CADDY BAG |
| 1 | CD-100 | CAULIDAU |