

Efficient Routing in Vehicular Adhoc Network: A Review

Manisha Doye, Heena Patankar, Shubhangi Kayalkar, Prof. Manjusha Talmale
Department of CSE, GNI Nagpur Maharashtra

Abstract - Vehicular ad hoc networks (VANETs) are a subgroup of mobile ad hoc networks (MANETs) with the distinguishing property that the nodes are vehicles like cars, trucks, buses and motorcycles. This implies that node movement is restricted by factors like road course, encompassing traffic and traffic regulations. Centralized solutions for vehicular traffic re-routing to alleviate congestion suffer from two intrinsic problems: scalability, as the central server has to perform intensive computation and communication with the vehicles in real-time; and privacy, as the drivers have to share their location as well as the origins and destinations of their trips with the server. In this paper we will review different work done by various researchers in the field of VANET.

Keywords - VANET, Security, Energy Efficiency

I. INTRODUCTION

Vehicular ad hoc networks (VANETs) are a subgroup of mobile ad hoc networks (MANETs) with the distinguishing property that the nodes are vehicles like cars, trucks, buses and motorcycles. This implies that node movement is restricted by factors like road course, encompassing traffic and traffic regulations. Because of the restricted node movement it is a feasible assumption that the VANET will be supported by some fixed infrastructure that assists with some services and can provide access to stationary networks. The fixed infrastructure will be deployed at critical locations like slip roads, service stations, dangerous intersections or places well-known for hazardous weather conditions.

Nodes are expected to communicate by means of North American DSRC standard that employs the IEEE 802.11p standard for wireless communication. To allow communication with participants out of radio range, messages have to be forwarded by other nodes (multi-hop communication). Vehicles are not subject to the strict energy, space and computing capabilities restrictions normally adopted for MANETs. More challenging is the potentially very high speed of the nodes (up to 250 km/h) and the large dimensions of the VANET.

The primary VANET's goal is to increase road safety. To achieve this, the vehicles act as sensors and exchange warnings or – more generally – telematics information (like current speed, location or ESP activity) that enables the drivers to react early to abnormal and potentially dangerous situations like accidents, traffic jams or glaze. The information provided by other vehicles and stationary infrastructure might also be used for driver assistant systems like adaptive cruise control (ACC) or breaking assistants. In addition, authorized entities like police or firefighters should be able to send alarm signals and instructions e.g. to clear

their way or stop other road users. Besides that, the VANET should increase comfort by means of value-added services like location based services or Internet on the road.

The recent adoption of the various 802.11 wireless standards has caused a dramatic increase in the number of wireless data networks. Today, wireless LANs are highly deployed and the cost for wireless equipment is continuing to drop in price. Currently, an 802.11 adapter or access point (AP) can be purchased for next to nothing. As a result of the high acceptance of the 802.11 standards, academia and the commercial sector are looking for other applicable solutions for these wireless technologies. Mobile ad hoc networks (MANET) are one area that has recently received considerable attention. One promising application of mobile ad hoc networks is the development of vehicular ad hoc networks (VANET).

A MANET is a self-forming network, which can function without the need of any centralized control. Each node in an ad hoc network acts as both a data terminal and a router. The nodes in the network then use the wireless medium to communicate with other nodes in their radio range. A VANET is effectively a subset of MANETs. The benefit of using ad hoc networks is it is possible to deploy these networks in areas where it isn't feasible to install the needed infrastructure. It would be expensive and unrealistic to install 802.11 access points to cover all of the roads in the United States. Another benefit of ad hoc networks is they can be quickly deployed with no administrator involvement. The administration of a large scale vehicular network would be a difficult task. These reasons contribute to the ad hoc networks being applied to vehicular environments. Traffic fatalities are one of the leading causes of death in the United States. The Federal Communications Commission (FCC), realizing the problem of traffic fatalities in the US dedicated 75 MHz of the frequency spectrum in the range 5.850 to 5.925 GHz to be used for vehicle to vehicle and vehicle to roadside communication. The 5.9 GHz spectrum was termed Dedicated Short Range Communication (DSRC) and is based on a variant of 802.11a. Seven channels of 10 MHz each make up DSRC, with six of the channels being used for services and one channel for control. The goal of the project is to enable the driver of a vehicle to receive information about their surrounding environment. The control channel is used to broadcast safety messages e.g. to alert the driver of potentially hazardous road conditions. The control channel is also used to announce the services that are available. If vehicle finds a service of interest on the control channel, it then switches to one of the service channels to use the service. A number of additional value added features are to be provided by the service channels such as the announcement of places of interest in the driver's locations e.g. restaurants in the area or gas prices.

II. LITERATURE SURVEY

This paper looks into the possibility of using the regular traffic patterns provided by public buses to improve the performance of Mobile Ad-hoc Networks (MANET) for Inter-vehicular communications systems (IVCS). MANET is an adhoc network with mobile nodes that are random and unpredictable. IVCS provide drivers and passengers with a range of services, and implementation of IVCS is possible using MANET. However, certain differences in the properties of nodes affect the performance. This performance degradation would be discussed in this paper through the results that are obtained from NS-2 simulations in a suggested Metropolitan GRID (M-GRID) scenario that attempts to simulate the physical traffic situation in a small part of any typical metropolitan environment. In view of this, a novel approach named BUSNet is introduced. This approach utilizes the deterministic nature of bus routes or any other public transport system to incorporate a mobile backbone infrastructure that improves the performance of IVCS using MANET.[1]

The vehicular ad hoc network (VANET) has attracted a lot of interest recently. However, traditional VANET is just an instantiation of MANET in which nodes are treated equally for data delivery. We first analyze the unique features of urban VANET that vehicles have different types, and move as clusters due to the influence of traffic lights. Then a two tier architecture called Mobile Infrastructure Based VANET (MIVANET) is proposed. In this architecture, the buses constitute a mobile backbone for data delivery while the low tier is composed of ordinary cars and passengers. MIVANET will not only bring the benefit that ordinary cars do not have to forward packets for other nodes, but also improve the network connectivity. The corresponding Mobile Infrastructure Registering (MIRG) and Mobile Infrastructure Routing (MIRT) algorithms are also presented. The bus line information is made full use in MIRT. Simulation results show that there is a 40-55% improvement in delivery ratio while the throughput is even doubled compared to GPSR in traditional VANET.[2]

Due to recent development in wireless communication networks, researches in Vehicular Ad-hoc Networks (VANETs) have been getting much attention on information sharing and service discovery. However, due to the ever-shifting mobility of vehicle topology, vehicles moving in non-fixed routes may not find suitable next-hop vehicles to pass the data. This paper proposes schemes to effectively circulate and discover service information with the aid of public transportation systems. Bus routes can be used to create a backbone structure and data can be posted and circulated on the structure to avoid the broadcast storm problem. Moreover, by adopting the proposed architecture, the required data can be effectively disseminated and discovered through the traffic infrastructure and mobile vehicles. The experiment results demonstrate that our scheme outperforms other schemes in terms of packet delivery ratio and end-to-end delay. Moreover, the overhead

of our scheme outperforms other scheme with an increasing of number of service requests.[3]

Vehicular ad hoc networks (VANETs) represent promising technologies for improving driving safety and efficiency. Due to the highly dynamic driving patterns of vehicles, it has been a challenging research problem to achieve effective and time-sensitive data forwarding in vehicular networks. In this paper, a Shared-Trajectory-based Data Forwarding Scheme (STDFS) is proposed, which utilizes shared vehicle trajectory information to address this problem. With access points sparsely deployed to disseminate vehicles' trajectory information, the encounters between vehicles can be predicted by the vehicle that has data to send, and an encounter graph is then constructed to aid packet forwarding. This paper focuses on the specific issues of STDFS such as encounter prediction, encounter graph construction, forwarding sequence optimization and the data forwarding process. Simulation results demonstrate the effectiveness of the proposed scheme.[4]

There has been increasing interest in the issue of multi-item queries in wireless broadcasting systems recently. Query starvation and bandwidth utilization have been identified as key issues for improved performance. In this paper, we examine this problem in the context of VANETs with multiple cooperating Road Side Units (RSUs). We characterize a query with two deadlines: Query Total Deadline (QTD) which is the actual deadline of a query and Query Local Deadline (QLD) which is the duration a query is valid for serving in an RSU. By considering these two deadlines together with vehicle speed, RSU range and inter-RSU distance, we formulate a Cooperative Query Serving (CQS) scheme which allows multiple RSUs to share residual bandwidth and effectively address the query starvation as well as the bandwidth utilization problems, hence maximizing the chance of serving multiple items queries. Extensive simulation results confirm that CQS outperforms other existing scheduling algorithms[5].

III. CONCLUSION

The central server has to perform intensive computation (to re-assign vehicles to new paths) and communication with the vehicles (to send the paths and to receive location updates) in real-time. This can make centralized solutions infeasible for large regions with many vehicles. Second, in a centralized architecture, the server requires the real-time locations as well as the origins and destinations of the vehicles to estimate the traffic conditions and provide effective individual re-routing guidance. This leads to major privacy concerns for the drivers and may prevent the adoption of such solutions due to "big brother" fears.

IV. REFERENCES

- [1]. Bazzan, D. Cagara, and B. Scheuermann. An evolutionary approach to traffic assignment. In Proceedings of the IEEE Symposium on Computational Intelligence in Vehicles and Transportation Systems (CIVTS), pages 43–50, 2014.
- [2]. M. Behrisch, L. Bieker, J. Erdmann, and D. Krajzewicz. Sumo - simulation of urban mobility: An overview. In Proceedings of

- the 3rd International Conference on Advances in System Simulation (SIMUL 2011), pages 63–68, Barcelona, Spain, 2011.
- [3]. A. Broder and M. Mitzenmacher. Network applications of bloom filters: A survey. *Internet Mathematics*, 1(4):485–509, 2004.
 - [4]. Y.C. Chiu, J. Bottom, M. Mahut, A. Paz, R. Balakrishna, T. Waller, and J. Hicks. Dynamic traffic assignment: A primer. *Transportation Research E-Circular*, (E-C153), 2011.
 - [5]. R. Dingledine, N. Mathewson, and P. Syverson. Tor: The second generation onion router. Technical report, Naval Research Lab Washington DC, 2004.
 - [6]. J. Gao, J. Han, D. Yang, and T. Wang. Road network based adaptive query evaluation in vanet. In *Mobile Data Management, 2008. MDM'08. 9th International Conference on*, pages 49–56. IEEE, 2008.
 - [7]. C. Gawron. Simulation-based traffic assignment computing user equilibria in large street networks. PhD thesis, University of Cologne, 1999.
 - [8]. B. Gedik and L. Liu. Protecting location privacy with personalized k-anonymity: Architecture and algorithms. *Mobile Computing, IEEE Transactions on*, 7(1):1–18, 2008.
 - [9]. M. Gruteser and D. Grunwald. Anonymous usage of location based services through spatial and temporal cloaking. In *Proceedings of the 1st international conference on Mobile systems, applications and services*, pages 31–42. ACM, 2003.