


Split System Cooling Single Phase – 1½-5 Tons



**XR13
(Single Stage)**

Table SC-5-C — XR13 R-410A Split System Single Stage Cooling

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size (in)	
			H	W	D					OD Gas	OD Liq.
4TTR3018G1000A	208/230/1/60	17,000	29	33	30	167	70	12	20	5/8	3/8
4TTR3024G1000A	208/230/1/60	23,000	29	33	30	169	71	17	25	5/8	3/8
4TTR3030G1000A	208/230/1/60	28,500	29	33	30	180	71	19	30	3/4	3/8
4TTR3036E1000A	208/230/1/60	34,500	33	33	30	197	71	22	35	3/4	3/8
4TTR3042D1000A	208/230/1/60	40,500	29	37	34	228	74	26	45	3/4	3/8
4TTR3048D1000A	208/230/1/60	46,500	29	37	34	235	75	28	50	7/8	3/8
4TTR3060D1000A	208/230/1/60	58,500	37	37	34	261	75	35	60	7/8	3/8

① 1 compressor, 2 stages.

* Information subject to change. Please confirm with current Product Data/Service Facts for current factory production.

** Rated in accordance with AHRI Standard 270-2008 (Min/Max when applicable).



It's Hard To Stop A Trane.®

Split System Cooling Single Phase – 1½-5 Tons

Table SC-6-A — Features

			XR13 (4TTR3)
• SEER up to			14.50
• Climatuff™ compressor			✓
• Number of stages.....			1
• Comfort-R™ mode approved.....			✓
• DuraTuff™ base, fast complete drain, weatherproof			✓
• Quick-Sess™ cabinet, service access & refrigerant connections with full coil protection.....			✓
• Spine Fin™ coil.....			✓
• Compressor sound enclosure			—
• Factory supplied charge			R-410A
• Glossy corrosion resistant finish			✓
• High pressure switch.....			✓
• Internal high / low pressure & temperature protection			✓
• Liquid line filter drier - factory installed or factory supplied for field install.....			✓
• Start kit - factory installed.....			—
• Tarpaulin gray cabinet			✓
• 10-year registered limited warranty on compressor, outdoor coil & all other functional parts (Residential Use)③			✓
• Extended warranties available			✓


Table SC-6-B — Optional Accessories

Model Number	Description	Shipping Weight	
AY28X079.....	Evap. Defrost Control Kit	1.....	✓
BAYCCHT300	Crankcase Heater Kit (Reciprocating)	1.....	1½-3
BAYCCHT301	Crankcase Heater Kit (Scroll)	1.....	3½-5
BAYCCHT302	Crankcase Heater Kit (Scroll)	1.....	—
BAYECMT023	Extreme Conditions Mounting Kit (Base 2/3)	2.....	1½-3
BAYECMT004	Extreme Conditions Mounting Kit (Base 4).....	2.....	3½-5
BAYISLT101	Rubber Isolators.....	1.....	✓
BAYKSKT263	Start Kit	1.....	✓
BAYKSKT266	Start Kit	1.....	—
BAYLEGS002	Snow Legs - Base and Cap 6" High (Black)	1.....	✓
BAYLEGS003	4" Extension (Black).....	1.....	✓
BAYLOAM103	Low Ambient Kit.....	1.....	✓
BAYSDEN003	Small Scroll Compressor Enclosures	8.....	1½-4
BAYSDEN004	Small Scroll Compressor Enclosures	5
BAYSEAC001.....	Seacoast Kit	1.....	✓
TAYASCT501A①②	Anti-Short Cycle Timer.....	2.....	✓
PAI00309④.....	Heresite Spraypaint	1.....	✓

Comfort Controls — See Comfort Controls/Zone Sensors Section

- ① Not for use with programmable thermostats.
- ② Activated on Power Off.
- ③ Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at trane.com or by phone at 800-554-6413; otherwise Trane Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on Comfortsite.com.
- ④ Used for additional seacoast corrosion protection. Refer to bulletin number UN-SVB11A-EN for application information.

Split System Cooling Single Phase – 1½-5 Tons



XB13
(Single Stage)

Table SC-7-C — XB13 R-410A Split System Single Stage Cooling

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size (in)	
			H	W	D					OD Gas	OD Liq.
4TTB3018H1000A	208/230/1/60	17,000	29	29	26	150	74	12	20	¾	¾
4TTB3024H1000A	208/230/1/60	23,000	29	29	26	150	74	18	30	¾	¾
4TTB3030G1000A	208/230/1/60	28,500	29	33	30	180	76	19	30	¾	¾
4TTB3036E1000A	208/230/1/60	34,500	29	33	30	186	74	20	35	¾	¾
4TTB3042D1000C	208/230/1/60	40,500	29	37	34	228	79	26	45	¾	¾
4TTB3048D1000C	208/230/1/60	46,500	29	37	34	235	79	28	50	7/8	¾
4TTB3060D1000D	208/230/1/60	58,500	37	37	34	261	80	35	60	7/8	¾

① 1 compressor, 2 stages.

* Information subject to change. Please confirm with current Product Data/Service Facts for current factory production.

** Rated in accordance with AHRI Standard 270-2008.



It's Hard To Stop A Trane.®

Split System Cooling Single Phase – 1½-5 Tons

Table SC-8-A — Features

			XB13 (4TTB3)
• SEER up to			14.00
• Comfort-R™ mode approved.....			✓
• DuraTuff™ base, fast complete drain, weatherproof			✓
• Quick-Sess™ cabinet, service access & refrigerant connections with full coil protection.....			✓
• Spine Fin™ coil			✓
• Refrigerant			R-410A
• Glossy corrosion resistant finish			✓
• High pressure switch			✓
• Compressor sound enclosure			—
• Internal high / low pressure & temperature protection			✓
• Liquid line filter drier - factory installed or factory supplied for field install			✓
• Polyslate gray cabinet			✓
• Tarpolan Gray Cabinet			—
• Start kit - factory installed.....			—
• 10-year registered limited warranty on compressor, outdoor coil & all other functional parts (Residential Use)③			✓
• Extended warranties available			✓


Table SC-8-B — Optional Accessories

Model Number	Description	Shipping Weight			
AY28X079.....	Evap. Defrost Control Kit	1			✓
BAYCCHT300	Crankcase Heater Kit (Reciprocating)	1			—
BAYCCHT301	Crankcase Heater Kit (Scroll)	1			3½-5
BAYCCHT302	Crankcase Heater Kit (Scroll)	1			1½-3
BAYECMT023	Extreme Conditions Mounting Kit (Base 2/3).....	2			1½-3
BAYECMT004	Extreme Conditions Mounting Kit (Base 4)	2			3½-5
BAYECMT021	Extreme Conditions Mounting Kit (XB300)			—
BAYISLT101	Rubber Isolators.....	1			✓
BAYKSKT263	Start Kit			✓
BAYKSKT266	Start Kit	1			—
BAYLEGS002	Snow Legs - Base and Cap 6" High (Black)	1			✓
BAYLEGS003	4" Extension (Black)	1			✓
BAYLOAM103	Low Ambient Kit	1			✓
BAYSDEN003	Small Scroll Compressor Enclosures.....	8			1½-4
BAYSDEN004	Large Scroll Compressor Enclosures	8			5
BAYSEAC001	Seacoast Kit	1			✓
TAYASCT501A①②	Anti-Short Cycle Timer	2			✓
PAI00309⑤.....	Heresite Spraypaint.....	1			✓

Comfort Controls — See Comfort Controls/Zone Sensors Section

- ① Not for use with programmable thermostats.
- ② Activated on Power Off.
- ③ Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at trane.com or by phone at 800-554-6413; otherwise Trane Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on Comfortsite.com.
- ④ For applications requiring the BAYLOAM103, an 8x8 weatherproof electrical enclosure is required in order to locate the low ambient controller external to the unit.
- ⑤ Used for additional seacoast corrosion protection. Refer to bulletin number UN-SVB11A-EN for application information.

Split System Cooling Three Phase and R-22



XB13
(Single Stage)

Table SC-9-C — R-22 Split System Dry Ship Replacement Single Stage Cooling

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size (in)	
			H	W	D					OD Gas	OD Liq.
2TTB3018A1000C	208/230/1/60	17,000	26	29	26	182	76	8	15	5/8	1/4
2TTB3024A1000C	208/230/1/60	23,000	33	29	26	195	78	12	20	3/4	5/16
2TTB3030A1000C	208/230/1/60	28,500	33	33	30	225	78	13	20	3/4	5/16
2TTB3036A1000C	208/230/1/60	34,500	33	33	30	205	76	21	35	7/8	3/8
2TTB3042A1000C	208/230/1/60	40,500	33	37	34	283	79	21	35	7/8	3/8
2TTB3048A1000C	208/230/1/60	46,500	41	37	34	307	79	25	40	1 1/8	3/8
2TTB3060A1000C	208/230/1/60	58,500	41	37	34	280	79	33	50	1 1/8	3/8

① 2TTM3018-030 units combined with indoor coils having non-equalizing expansion valves may require the use of a hard start or start assist kit. Follow the outdoor unit manufacturer's guidelines.

* Information subject to change. Please confirm with current Product Data/Service Facts for current factory production.

** Rated in accordance with AHRI Standard 270-2008.



Split System Cooling Three Phase and R-22

Table SC-10-A— Features

		XB13 (2TTB3)
• SEER up to		13.25
• Comfort-R™ mode approved.....		✓
• DuraTuff™ base, fast complete drain, weatherproof		✓
• Quick-Sess™ cabinet, service access & refrigerant connections with full coil protection.....		✓
• Spine Fin™ coil.....		✓
• Compressor sump heat - factory installed		—
• Refrigerant - (R-22 not factory supplied).....		R-22
• Glossy corrosion resistant finish		✓
• High pressure switch.....		—
• Compressor sound enclosure		3½
• Internal high / low pressure & temperature protection		✓
• Liquid line filter drier - factory installed or factory supplied for field install		✓
• Low pressure switch.....		—
• Polyslate gray cabinet		✓
• Tarpolan gray cabinet.....		—
• Start kit - factory installed.....		1½-2½,3½-4
• 5-year registered limited warranty on compressor, outdoor coil and 1-year on all other functional parts (Commercial Use)		—
• 5-year registered limited warranty on compressor, outdoor coil & all other functional parts (Residential Use)④		✓
• Extended warranties available		✓


Table SC-10-B — Optional Accessories

Model Number	Description	Shipping Weight	
AY28X079.....	Evaporator Defrost Control.....	1.....	✓
BAY24X045.....	Indoor Fan Delay Kit.....	1.....	—
BAYCCHT300.....	Crankcase Heater Kit (Reciprocating).....	1.....	1½-2½,3½-4
BAYCCHT301.....	Crankcase Heater Kit (Scroll).....	1.....	3,5
BAYECMT023.....	Extreme Conditions Mounting Kit (Base 2/3).....	2.....	1½-3
BAYECMT004.....	Extreme Conditions Mounting Kit (Base 4).....	2.....	3½-5
BAYECMT021.....	Extreme Conditions Mounting Kit (XB300).....	—
BAYISLT101.....	Rubber Isolators.....	1.....	✓
BAYKSKT263.....	Start Kit.....	5
BAYKSKT260.....	Start Kit.....	1.....	3
BAYLEGS002.....	Snow Legs - Base and Cap 6" High (Black).....	1.....	✓
BAYLEGS003.....	4" Extension (Black).....	1.....	✓
BAYLOAM103.....	Low Ambient Kit.....	1.....	✓
BAYSDEN001.....	Single Cylinder Compressor Enclosures.....	8.....	1½-2½
BAYSDEN003.....	Small Scroll Compressor Enclosures.....	8.....	3
BAYSDEN004.....	Large Scroll Compressor Enclosures.....	8.....	5
BAYSEAC001.....	Seacoast Kit.....	1.....	✓
TAYASCT501A①②.....	Anti-Short Cycle Timer.....	2.....	✓
PAI00309③.....	Heresite Spraypaint.....	1.....	—

Comfort Controls — See Comfort Controls/Zone Sensors Section

- ① Do not use with programmable thermostats.
- ② Activated on Power Off.
- ③ Used for additional seacoast corrosion protection. Refer to bulletin number UN-SVB11A-EN for application information.
- ④ Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at trane.com or by phone at 800-554-6413; otherwise Trane Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on Comfordsite.com.
- ⑤ For applications requiring the BAYLOAM103, an 8x8 weatherproof electrical enclosure is required in order to locate the low ambient controller external to the unit.

Split System Heat Pumps Single Phase – 1½-5 Tons



**XR13
(Single Stage)**

Table SH-5-C — XR13 R-410A Split System Single Stage Heat Pump

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size (in)	
			H	W	D					OD Gas	OD Liq.
4TWR3018D1000A	208/230/1/60	17,200	29	33	30	185	71	12	20	5/8	3/8
4TWR3024D1000A	208/230/1/60	22,000	29	33	30	184	71	17	25	5/8	3/8
4TWR3030C1000A	208/230/1/60	28,500	33	33	30	221	76	15	25	3/4	3/8
4TWR3036C1000A	208/230/1/60	35,800	33	37	34	229	73	22	35	3/4	3/8
4TWR3042B1000A	208/230/1/60	40,500	33	37	34	253	75	26	45	3/4	3/8
4TWR3048B1000A	208/230/1/60	46,500	37	37	34	269	75	28	50	7/8	3/8
4TWR3060B1000A	208/230/1/60	58,500	41	37	34	284	75	34	60	7/8	3/8

* Information subject to change. Please confirm with current Product Data/Service Facts for current factory production.

** Rated in accordance with AHRI Standard 270-2008.



Split System Heat Pumps Single Phase – 1½-5 Tons

Table SH-6-A — Features

			XR13 (4TWR3)
• SEER up to			14.50
• HSPF up to			8.50
• Climatuff™ compressor			✓
• Comfort-R™ mode approved			✓
• DuraTuff™ base, fast complete drain, weatherproof			✓
• Quick-Sess™ cabinet, service access & refrigerant connections with full coil protection			✓
• Spine Fin™ coil			✓
• Compressor sound enclosure			—
• Compressor sump heat - factory installed			—
• Factory supplied charge			R-410A
• Glossy corrosion resistant finish			✓
• High pressure switch			✓
• Low pressure switch			✓
• Internal high / low pressure & temperature protection			✓
• Liquid line filter drier - factory installed			✓
• Start kit - factory installed			2½
• Tarpaulin gray cabinet			✓
• 10-year registered limited warranty on compressor, outdoor coil & all other functional parts (Residential Use)³			✓
• Extended warranties available			✓

Table SH-6-B — Optional Accessories

Model Number	Description	Shipping Weight	
AY28X084.....	Evap. Defrost Control Kit	1.....	✓
BAYCCHT300	Crankcase Heater Kit	1.....	2½
BAYCCHT301	Crankcase Heater Kit	1.....	3½-5
BAYCCHT302	Crankcase Heater Kit	1.....	1½,2,3
BAYECMT023	Extreme Conditions Mounting Kit (Base 2/3).....	2.....	1½-2½
BAYECMT004	Extreme Conditions Mounting Kit (Base 4).....	2.....	3-5
BAYISLT101	Rubber Isolators.....	1.....	✓
BAYKSKT263	Start Kit (Scroll)	1.....	1½-2,3-5
BAYKSKT266	Start Kit (Scroll)	1.....	—
BAYLEGS002	Snow Legs - Base and Cap 6" High (Black)	1.....	✓
BAYLEGS003.....	4" Extension (Black)	1.....	✓
BAYLOAM103	Low Ambient Kit	1.....	✓
BAYSDEN001	Single Cylinder Compressor Enclosures8.....	—
BAYSDEN003	Small Scroll Compressor Enclosures.....	.8.....	1½-4
BAYSDEN004	Large Scroll Compressor Enclosures8.....	5
BAYSEAC001	Seacoast Kit	1.....	✓
TAYASCT501A①②.....	Anti-Short Cycle Timer2.....	✓
PAI00309⑤.....	Heresite Spraypaint.....	1.....	✓


Comfort Controls — See Comfort Controls/Zone Sensors Section

- ① Do not use with programmable thermostats.
- ② Activated on Power Off.
- ③ Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at trane.com or by phone at 800-554-6413; otherwise Trane Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on Comfortsite.com.
- ④ For operation to 20°F outdoor ambient.
- ⑤ Used for additional seacoast corrosion protection. Refer to bulletin number UN-SVB11A-EN for application information.



It's Hard To Stop A Trane.®


Split System Heat Pumps Single Phase – 1½-5 Tons



**XB14
(Single Stage)**

Table SH-7-A — XB14 R-410A Split System Single Stage Heat Pump

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size (in)	
			H	W	D					OD Gas	OD Liq.
4TWB4018G1000B	208/230/1/60	18,000	29	33	30	204	76	9	15	5/8	3/8
4TWB4024G1000B	208/230/1/60	24,000	33	33	30	236	76	11	15	5/8	3/8
4TWB4030G1000B	208/230/1/60	30,000	33	37	34	273	78	15	25	3/4	3/8
4TWB4036G1000B	208/230/1/60	36,000	33	37	34	261	76	18	30	3/4	3/8
4TWB4042G1000B	208/230/1/60	41,500	37	37	34	277	76	23	40	3/4	3/8
4TWB4049E1000C	208/230/1/60	48,000	45	37	34	331	76	28	50	7/8	3/8
4TWB4061E1000C	208/230/1/60	60,000	45	37	34	332	76	36	60	1 1/8	3/8



**XB13
(Single Stage)**

Table SH-7-B — XB13 R-410A Split System Single Stage Heat Pump

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size (in)	
			H	W	D					OD Gas	OD Liq.
4TWB3018D1000A	208/230/1/60	16,800	29	33	30	184	76	12	20	5/8	3/8
4TWB3024D1000A	208/230/1/60	22,000	29	33	30	184	76	17	25	5/8	3/8
4TWB3030C1000A	208/230/1/60	28,500	33	33	30	221	79	15	25	3/4	3/8
4TWB3036C1000A	208/230/1/60	35,800	33	37	34	229	76	22	35	3/4	3/8
4TWB3042B1000C	208/230/1/60	40,500	33	37	34	253	79	26	45	3/4	3/8
4TWB3048B1000C	208/230/1/60	46,500	37	37	34	269	78	28	50	7/8	3/8
4TWB3060B1000C	208/230/1/60	58,500	41	37	34	284	78	34	60	7/8	3/8

* Information subject to change. Please confirm with current Product Data/Service Facts for current factory production.

** Rated in accordance with AHRI Standard 270-2008.



It's Hard To Stop A Trane.®

Split System Heat Pumps Single Phase – 1½-5 Tons

Table SH-8-A — Features

	XB14 (4TWB4)	XB13 (4TWB3)
• SEER up to	15.00	14.00
• HSPF up to	9.0	8.5
• Comfort-R™ mode approved	✓	✓
• DuraTuff™ base, fast complete drain, weatherproof	✓	✓
• Quick-Sess™ cabinet, service access & refrigerant connections with full coil protection	✓	✓
• Spine Fin™ coil	✓	✓
• Compressor sound enclosure	3	—
• Compressor sump heat - factory installed	4-5	—
• Refrigerant - (R-22 not factory supplied)	R-410A	R-410A
• Glossy corrosion resistant finish	✓	✓
• High pressure switch	✓	✓
• Low pressure switch	3½-5	1½-2, 3-5
• Liquid line filter drier - factory installed	✓	✓
• Polyslate gray cabinet	✓	✓
• Start kit - factory installed	1½-3	2½
• 10-year registered limited warranty on compressor, outdoor coil & all other functional parts (Residential Use) ③	✓	✓
• Extended warranties available	✓	✓

Table SH-8-B — Optional Accessories

Model Number	Description	Shipping Weight		
AY28X084.....	Evaporator Defrost Control HP	1	✓	✓
BAYCCHT300	Crankcase Heater Kit (Recip)	1	1½-3½	2½
BAYCCHT301	Crankcase Heater Kit (Scroll).....	—	3½-5
BAYCCHT302	Crankcase Heater Kit (Scroll).....	—	1½,2,3
BAYECMT023	Extreme Conditions Mounting Kit (Base 2/3)	2	—	1½-2½
BAYECMT004	Extreme Conditions Mounting Kit (Base 4)	2	✓	3-5
BAYISLT101	Rubber Isolators	1	✓	✓
BAYKSKT263	Start Kit (Scroll)	1	3½-5	1½-2,3-5
BAYLEGS002	Snow Legs - Base and Cap 6" High (Black)	1	✓	✓
BAYLEGS003	4" Extension (Black)	1	✓	✓
BAYLOAM103	Low Ambient Kit	1	✓④	✓
BAYSDEN001	Single Cylinder Compressor Enclosures	8	1½-2½	—
BAYSDEN003	Small Scroll Compressor Enclosures	8	3½-5	1½-4
BAYSDEN004	Large Scroll Compressor Enclosures	8	—	5
BAYSEAC001	Seacoast Kit	1	✓	✓
TAYASCT501A①②	Anti-short cycle timer	2	✓	✓
PAI00309⑤.....	Heresite Spraypaint.....	1	✓	✓

Comfort Controls — See Comfort Controls/Zone Sensors Section

- ① Do not use with programmable thermostats.
- ② Activated on Power Off.
- ③ Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at trane.com or by phone at 800-554-6413; otherwise Trane Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on Comfordsite.com.
- ④ For operation to 20°F outdoor ambient.
- ⑤ Used for additional seacoast corrosion protection. Refer to bulletin number UN-SVB11A-EN for application information.