



ATX GRIP Custom Easy X Y Vibration Isolator

Austin Office:
9201 Brown Ln Suite 290
Austin, Tx 78754
Austin Office Phone:
512-537-4201
832-651-3053
Austin Office Email:
Rentals@atxgrip.com

**Dampening Axis X, and Y
Tunable Dampening**

Over or Underslung

Specification:

Weight: 6.3kgs /14lbs (basic version)

Payload: up to 85kgs/189lbs

Temperature range from -20° to +50°C / -4° to +122° F (with hydraulic shocks)

Dimensions (L x W x H): 320 x 320 x 160 mm

Supports Mitchell and Bowl (coming soon) camera heads.

Interchangeable Mitchell base mounts

Raptor XY2 absorbs pulsations in the X & Y horizontal axis. Smoother shots without disturbing vibrations are the result.

DRAG & LOCK ADJUSTMENT

The standard springs provide a substantial reduction in abrupt stops and help smoothen out movement ends.

Adjustable hydraulic shocks can be installed to increase the setting range; and drag adjustment and a complete lock off is possible.

VERSATILE OPERATION

Raptor XY is flexible while supporting payloads up to 85kgs! Thanks to overslung or upright operation via Mitchell mounting based, this XY equips quickly with a suite of keygrips meet the director's shooting requirements.

Compatible rigs: car-mount, shock absorber arm, dolly, tripod...



