

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

TIMBERLINE

TECHNICAL CHARACTERISTICS

Available Formats:	8x36, 5x36, 3x36 (All in one box)		
Style Description:	Multi-width Plank	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Wood	Number of Faces/Screens:	8
Thickness in mm:	10.7	Number of Punches/Molds:	N/A
Modular Suitability:	Yes	Body Type:	Porcelain (<.5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	No less than 1/8"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< .5%	Static COF:	Wet: 0.60 Dry: 0.60
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	N/A	Breaking Strength:	2953
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Class 3
Chemical Resistance:	GA (V)		

PACKING INFORMATION - 20x20 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.62	Pieces per Carton:	9
SqFt per Pallet:	488.04	Pounds per Carton:	59.30 Lbs
Boxes per Pallet:	42	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".