

4-3/4" OD X 2.688" ID DRILL COLLAR, NON MAG SLICK, NMS 100, NC38

DRILL COLLAR BODY

Nominal OD (in)	4-3/4
Nominal ID (in)	2.688
Pipe Wall Thickness (in)	1.031
Surface Finish	NON MAG SLICK
Grade	NMS 100
Cross Sectional Area of Pipe Body (in ²)	12.046
Cross Sectional Area OD (in ²)	17.721
Cross Sectional Area ID (in ²)	5.675
Section Modulus (in ³)	9.443
Polar Section Modulus (in ³)	18.885
Momet of Inertia Drill Collar Body (in ⁴)	22.43
Polar Moment of Inertia Drill Collar Body (in ⁴)	44.85

DRILL COLLAR CONNECTION

Connection	NC38
OD (in)	4.750
ID (in)	2.688

DRILL COLLAR ASSEMBLY

Approx Average Length (ft)	31.00
Open End Displacement (gal/ft)	0.63
Closed End Displacement (gal/ft)	0.92
Fluid Capacity (gal/ft)	0.30
Drift Size (in)	2.563

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PST Energy Ltd. accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.