

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

CHICAGO

TECHNICAL CHARACTERISTICS

Available Formats:	4x8, 4x8 City Mix, 9x11 Hexagon, Modular 16x16, 8x16, 8x8; 3x16 Bullnose, 3x3 Staggered Mosaic 12x16 Sheet, 4x16x2 Stair Tread, 4x4 3/4x3 5/16 Corner		
Style Description:	Reclaimed Chicago Brick	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Brick	Number of Faces/Screens:	4x8: 56; Hex: 25
Thickness in mm:	10.5	Number of Punches/Molds:	N/A
Modular Suitability:	Yes (16x16, 8x16, 8x8 Only)	Body Type:	Porcelain (<.5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	Pre-consumer 20%	Surface Type:	Matte/Textured
Rectified:	No	Recommended Grout Joint:	No less than 3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< .5%	Static COF:	Wet: 0.60 Dry: 0.70
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.65
Scratch Hardness (MOHS)	7	Breaking Strength:	>1300N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Yes		

PACKING INFORMATION - 4x8 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	7.32	Pieces per Carton:	34
SqFt per Pallet:	572.04	Pounds per Carton:	33.44
Boxes per Pallet:	72	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".