

## Equiplite, Halyard(HB) / Snatch Blocks(SB)



### Hi load Snatch Block

**NEW:** all the snatch blocks with UV cover for fully UV protection for long life.

Equiplite Patd. snatch blocks use DSK 75 loops to take the loads directly through the centre of the sheave. This allows the blocks to be extremely light, compact, quick and easy to operate, compared to competitive blocks, of the same load. They employ carbon composite side plates, aluminium sheaves for Hi Load types and high load low friction polymer bearings.

They are used on top competitive boats for all uses, including Barber Haulers, tweakers etc. and their flexibility make them particularly good for the most difficult use on Halyards (from 2:1). Becketts and double sheaves also available.

- Advantages include:**
- \* extremely high loads and compact
  - \* Approx. 80% weight saving, compared to competitive blocks
  - \* Safer, light weight reduces risk of injury when flogging
  - \* Easy and quick to attach and detach, even with cold & wet hands
  - \* Reduced damage to masts, spinnaker tracks, topsides etc.
  - \* Will not jam even if overloaded, will operate close to break load.

Note: Dyneema cover are coated with UV coatings, exposure and wear due to usage however will reduce strength. It is recommended that Loops should be replaced every three years under normal usage. In sizing for heavy use, SWL should be conservative.

**All data approx and subject to change without notice.**  
Other sizes available on special order.

Unspecified dims. mm.  
Break Load approx. 1.8 to 2 x SWL.

Part	Sheave Ø is approx		*Other throats available		
	Sheave Ø	Max work line (mm / ")	Throat (mm / ")	SWL (Kg / Lb)	Weight (Gm / ")
50-150-18 HB/SB-HL	150	35	65	35000 / 70000	2.400
50-135-16 HB/SB-HL	135	35	60	26000 / 52000	2.100
50-125-14 HB/SB-HL	125	35	55	19000 / 44000	1.950
50-120-12 HB/SB-HL	120	35	55	15000 / 33000	1.700
35-120-12 HB/SB-HL	120	26	47	15000 / 33000	1.527
35-95-12 HB/SB-HL	95	26	47	15000 / 33000	1.150
25-75-10 HB/SB-HL	75	22	45	9000 / 17600	585
25-75-10 HB/SB	75	22	45	4000 / 8800	450
20-65-8 HB/SB-HL	65	18	35	6500 / 11000	385
20-65-8 HB/SB	65	18	35	2500 / 5500	342
16-46-6 HB/SB-HL	46	14	27	4000 / 8800	158
16-46-6 HB/SB	46	14	27	1800 / 4000	149
13-38-5 HB/SB-HL	38	12	20	3000 / 6000	97
13-38-5 HB/SB	38	12	20	1400 / 3100	89
10-30-4 HB/SB-HL	30	8	17	2500 / 4400	48
10-30-4 HB/SB	30	8	17	1000 / 2200	44

Above HL= Hi Load version employing hi load low friction polymer be

all details approximate  
HB = Halyard block    SB = Snatch block

Roller bearings and other types available on special order.