

TECHNICAL DATA

HIGH PURITY PRECISION ELECTRONIC

CONTACT CLEANER

AREAS OF USE:

- I & E SHOPS
- PULP & PAPER MILLS
- PETRO-CHEMICAL PLANTS
- FACTORIES
- MINES
- ELECTRIC MOTOR SHOPS
- MACHINE SHOPS
- SUGAR MILLS & REFINERIES
- STEEL MILLS

APPLICATIONS:

- ELECTRIC MOTORS
- ELECTRONIC PARTS
- CIRCUIT BOARDS
- MOTOR WINDINGS
- IGNITION SYSTEMS
- SWITCHES & RELAYS
- JUNCTION BOXES
- COMPUTERS & RADIOS

TECHNICAL DATA:

COLOR: Clear

DETERGENCY: None

WETTING ABILITY: Negligible

STORAGE STABILITY: 1 Year +

COLD STABILITY: 0° F

PHOSPHATES: None

PROPELLENT: CO₂

FLASH POINT: None

FLAME EXTENSION: None

SOLUBILITY IN WATER: 0%

SPECIFIC GRAVITY: 1.25

% VOLATILE BY VOLUME: 100%

pH: None

EVAPORATION RATE: Rapid

*** READ AND UNDERSTAND THE MATERIAL SAFETY DATA SHEET ***

HMIS

HEALTH	2
FLAMMABILITY	0
REACTIVITY	0
PERSONAL	B

	NFPA	
HEALTH	0	FIRE HAZARD
HAZARD	2	REACTIVITY
	0	SPECIAL

EXCLUSIVELY DISTRIBUTED BY:

MINERALS TECH
4721 Paso Del Puma NE
Albuquerque, NM 87111-3076
(505) 238-0852

EMERGENCY PHONE:
505 238-0852
agrether@comcast.net



INDUSTRIAL ALLOYS CO.™
Division of INDALLOY INC.

HIGH PURITY CONTACT CLEANER

Stock No. CH025

- Contains No CFC's
- Safe for Most Plastics
- Non-Flammable
- 26,000 Volt Dielectric
- Non-Conductive
- Leaves No Residue

CAUTION

Contents under pressure.
KEEP OUT OF REACH OF CHILDREN.

CAN SIZE 14 OZ.
12 CANS PER CARTON

HIGH PURITY CONTACT CLEANER

Cleans oil, grease, dirt, condensation and moisture from circuit boards, precision instruments, oxygen equipment, controls, switches, motors and film. Can be used on the following plastics: Neoprene W, Buna N, Buna S, Silicone rubber, Butyl, Natural rubber, Thiokol FA, Hypalon 40, Viton A, Adlprene L, Nordel, Delrin resin, Zytel, Nylon, Teflon, PVC, Polyurethane. For other plastics, test inconspicuous spot first.

DIRECTIONS

Shake well and point spray opening away from face. Spray surface to be cleaned until well saturated. Operate switches or relays while being sprayed to assure complete cleaning. Current does not have to be turned off during application.

CAUTION: Use in well ventilated areas only, avoiding inhalation of mists or vapors. Do not store in direct sunlight or at temperatures above 120°F. Do not incinerate or puncture cans. **EYES:** Flush with water for 15 minutes.

INGREDIENTS: 1, 1-Dichloro-1-fluoroethane (CAS #1717-00-6), Carbon Dioxide (CAS #124-38-9)

MANUFACTURED FOR:

INDUSTRIAL ALLOYS CO.™

Division of Indalloy Inc.

No. 6 Truett Drive — Covington, LA 70435
(504) 893-7000

HIGH PURITY CONTACT CLEANER

A highly effective cleaning degreaser with less potential for ozone depletion than traditional contact and circuit board cleaners containing CFC's.