


**COLORS** 1. 90 BLACK  
 2. 335 DOT GREEN  
 3. 2975 BLUE  
 4. \_\_\_\_\_

**STYLE** CLOSED TOP   
 OPEN TOP   
 OTHER

**PART#** 68-295651B  
**CAD#** 68-3

**CERT-** 44 ECT

**BOARD-** WHITE   
 KRAFT



LEAD EDGE

FOR HVAC

**ATTENTION!!**  
 THIS IS A NON-REUSABLE CYLINDER!  
 IT IS EQUIPPED WITH A NON-REFILLABLE VALVE!  
 DO NOT REMOVE CYLINDER FROM CARTON!  
 DO NOT ATTEMPT TO REFILL WITH  
 COMPRESSED AIR OR ANY OTHER MATERIAL!  
 DISPOSE OF PROPERLY!



Net Wt.  
 30 Lbs. (13.6kg)



# 134a



**1,1,1,2-TETRAFLUOROETHANE**  
 CAS# 811-97-2

# 134a

**NON-FLAMMABLE GAS**

CYLINDER MANUFACTURED BY WORTHINGTON CYLINDER COLUMBUS, OHIO/USA

# 134a

INSIDE CONTAINER COMPLIES WITH PRESCRIBED SPECIFICATIONS  
 LE CONTENU DE L'EMBALLAGE EST CONFORME AUX NORMES PRESCRITES  
 ESTE CILINDRO CUMPLEM CON LAS ESPECIFICACIONES REQUERIDAS POR LA LEY

## 30 LB. 13.6 kg

**NON-RETURNABLE**  
 EMBALLAGE PERDU  
 CYLINDER DESECHABLE

**NON-REFILLABLE**  
 NE PAS REUTILISER  
 NO RELLENABLE

**DO NOT STORE ABOVE 120°F**  
**NE PAS STOCKER A PLUS DE 50°C**  
**NO ALMACENARLO SOBRE 50°C**

CYLINDER MANUFACTURED BY WORTHINGTON CYLINDER COLUMBUS, OHIO/USA

# 134a



**1,1,1,2-TETRAFLUOROETHANE**  
 CAS# 811-97-2

# 134a

**NON-FLAMMABLE GAS**

CYLINDER MANUFACTURED BY WORTHINGTON CYLINDER COLUMBUS, OHIO/USA

Cylinder Shall Not Be Removed From Carton

<b>R-134a</b> 1,1,1,2-Tetrafluoroethane	<b>WARNING:</b> Contains gas under pressure may explode if heated.  Protect from sunlight. Store in well ventilated place.
	See additional warnings and safe use instructions on carton.
Name Address Telephone # (responsible party of substance)	

**1,1,1,2-TETRAFLUOROETHANE** CAS# 811-97-2

**WARNING!**  
 Liquid and gas under pressure. Vapor reduces oxygen available for breathing, can cause rapid asphyxiation. Inhalation or misuse of product can result in serious personal injury or death. May decompose in contact with hot metal surfaces to release toxic, corrosive decomposition products. Contact of liquid with skin or eyes may cause irritation and frostbite. Overheating, pressurizing, or recharging can cause cylinder to burst, resulting in serious personal injury or death.

- Do not inhale vapors.
- Store and use with adequate ventilation, never in a closed space.
- Avoid contact with skin, eyes or clothing.
- Do not store in direct sunlight or heat above 120°F (50°C).
- Do not store in damp areas.
- Do not drop or subject this cylinder to rough handling.
- Do not tamper with safety relief device or valve.
- Before using, read corresponding Material Safety Data Sheet.

**FIRST AID**  
 If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Avoid stimulants. Do not give adrenaline (epinephrine). Call a physician.  
 In case of contact, flush eyes promptly with plenty of water for at least 15 minutes. Call a physician. Flush exposed skin with water (and hot) or use other means to warm skin slowly.

**INSTRUCTIONS FOR DISPOSAL**  
 Do not vent residual contents to the atmosphere. After use, to ensure cylinder is empty, use properly approved recovery or recycling equipment to evacuate all remaining gas. After empty, leave valve open and dispose of cylinder properly. This steel tank is recyclable. So please, where possible... recycle!

**134a**  
 NON-FLAMMABLE GAS

© 2014, Worthington Cylinder Corporation



68-295651B

