



Specifications		(The wire rope composition is a manufacturer recommendation.)		
Load Rating	9,800N (= 1,000kgf)	Handle Force	Handle Length	Number of Wire Rope Winding Layer
Wire Rope Tension	3rd Layer (Standard Layer)		300mm	
Drum Capacity	Wire Rope 5-Layer Windings φ 8mm (6 × 37), JIS × 35m	Wire Rope Tension	9,800N	
Gear Ratio	1 / 12.6	Standard Accessories		3rd Layer 182N (= 18.5kgf)
Effective Handle Length	300mm (Maximum)	Painting		One Handle
Weight	17.3kg (Winch + Handle)			One Hex Wrench for Anchoring the Wire Rope
Melamine Resin Coating At Two Layers				
Painting Color				
Drum : Black (Munsell N1 Semi Gloss)				
Others : Munsell 7.5YR6/11				

※To prevent irregular winding of the wire rope around the drum, keep the fleet angle 2 degrees or less.

Please install the pulley 2550mm or more away from the drum on the center line of the drum.

※The value of specified "Wire Rope Tension" on this drawing is for the standard layer or less.

The value of the "Wire Rope Tension" must be decreased accordance with the ratio of the actual winding layers, if it exceeded.

△ ×	..	図面番号 / DRAWING No.	MR10SI-160804-01E	改訂番号 / REVISION No.	00	お客様 / CUSTOMER	符号 / MARK	項目 / PARTICULARS	材料 / MATERIAL	数量 / QTY	単体合計 / PER ONE TOTAL	備考 / REMARKS
△ ×	..	承認 / APPROVED	検図 / CHECKED	作成 / DRAWN	図面名 / TITLE	MAXPULL WINCH STOPPER ARMLESS RATCHET TYPE MODEL MR-10-SI	投影法 / PROJECTION METHOD	第三角法 / THIRD ANGLE PROJECTION	尺度 / SCALE	台数 / QTY		
△ ×	..	設計部	設計部	設計部								
△ ×	..	'16.08.04	'16.08.04	'16.08.04								
改訂 / REVISION	..	米澤	松嶺	武松								

