

8-1/4" OD X 3.500" ID DRILL COLLAR, NON MAG SLICK, P530, 6-5/8" REG

DRILL COLLAR BODY

Nominal OD (in)	8-1/4
Nominal ID (in)	3.500
Pipe Wall Thickness (in)	2.375
Surface Finish	NON MAG SLICK
Grade	P530
Cross Sectional Area of Pipe Body (in ²)	43.835
Cross Sectional Area OD (in ²)	53.456
Cross Sectional Area ID (in ²)	9.621
Section Modulus (in ³)	53.341
Polar Section Modulus (in ³)	106.682
Momet of Inertia Drill Collar Body (in ⁴)	220.03
Polar Moment of Inertia Drill Collar Body (in ⁴)	440.06

DRILL COLLAR CONNECTION

Connection	6-5/8" REG
OD (in)	8.250
ID (in)	3.500

DRILL COLLAR ASSEMBLY

Approx Average Length (ft)	31.00
Open End Displacement (gal/ft)	2.28
Closed End Displacement (gal/ft)	2.78
Fluid Capacity (gal/ft)	0.50
Drift Size (in)	3.375

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PETRO PIPE accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.