



---

**ALL BALE SPEARS  
ARE NOT CREATED  
EQUAL!**

---

**CONSTRUCTED WITH PRIME  
THREE INCH SQUARE TUBING  
WITH A 1/4" WALL. FRAMES  
ARE FULLY WELDED, WITH A  
1/4" THICK FRONT GUSSET  
PLATE, AND 1/2" THICK CLEVIS  
STYLE LOWER ARM TABS.**

---

**WE FEATURE HEAVY DUTY  
FORGED ALLOY, HEAT  
TREATED, TAPERED BALE  
TINES. AVAILABLE IN  
DIFFERENT LENGTHS AND  
DIAMETERS. WE USE ONLY  
QUALITY GERMAN MADE  
SHW® BALE TINES.**

---

## **CENTRAL WELDING COMPANY**

109 W Main St  
Concord, Illinois 62631  
(217) 457-2354

Visit us online at:  
[www.centralweldingco.com](http://www.centralweldingco.com)

Email us at:  
[central.welding.co@gmail.com](mailto:central.welding.co@gmail.com)

# **HEAVY DUTY**

## **BALE SPEAR/TRAILER MOVER**

**(C2200/C2100)**







This is not your average bale spear. The attachments we manufacture are tough, just like they should be. The light weight bale spears offered by the competition may be fine for the hobby farmer, but we understand you're running a business and you need attachments that work just as hard as you do.

This three point bale spear will easily become one of the most versatile tools on your farm. Features include - a standard 2" hitch receiver, a 1/2" thick mounting tab for your gooseneck ball, and the most rugged construction of any comparable bale spear on the market. Designed to fit category II three point hitches, and quick hitches.

Covered by a full warranty against defect or component failure for a full year!

Standard model C2200 is rated for a hefty 2700 pounds and utilizes two conus 2, 49" tines rated at over 2,600 pounds apiece that are spaced 30 inches apart on center. Model C2100 uses one conus 2, 49" tine and two conus 1, 24" tines rated at nearly 1400 pounds apiece.



Photo	Model No.	Weight Rating	Unit Weight	Tines	Notes
	C2200	3000 lbs	140 lbs	<b>SHW 2-Conus 2, 49"</b> <b>(44 usable)</b> <b>Rated at 2697 lbs</b> <b>apiece</b> <b>Other sizes available</b>	<b>Available without</b> <b>trailer mover</b> <b>option, Fits Cat 2,</b> <b>Quick Hitch</b> <b>Compatible</b>
	C2100	3000 lbs	142 lbs	<b>SHW 1- Conus 2, 49"</b> <b>(44 usable)</b> <b>Rated at 2697 lbs</b> <b>Other sizes available</b> <b>SHW 2- Conus 1, 24"</b> <b>(19 usable)</b> <b>Rated at 1349 lbs</b> <b>apiece</b>	<b>Available without</b> <b>trailer mover</b> <b>option,</b> <b>Fits Cat 2, Quick</b> <b>Hitch Compatible</b>
	C4901	1500 lbs	70 lbs	<b>SHW 1- Conus 2, 49"</b> <b>(44 usable)</b> <b>Rated at 2697 lbs</b> <b>Other sizes available</b> <b>Solid steel stabilizer</b> <b>spikes.</b> <b>1.125" X 10"</b>	<b>No Trailer Mover</b> <b>Option, Fits Cat 1</b> <b>or 2,</b> <b>Quick Hitch</b> <b>Compatible</b>
	C3200	4000 lbs	210 lbs	<b>SHW 2-Conus 3, 49"</b> <b>(44 usable)</b> <b>Rated at 4469 lbs</b> <b>apiece</b>	<b>Available without</b> <b>trailer mover</b> <b>option,</b> <b>Fits Cat 3,</b> <b>Quick Hitch</b> <b>Compatible</b>
	CWC4900B	4000 lbs	198 lbs	<b>SHW 2-Conus 3, 49"</b> <b>(44 usable)</b> <b>Rated at 4469 lbs</b> <b>apiece,</b> <b>Other sizes available</b>	<b>No Trailer Mover</b> <b>Option, Fits Cat 2</b> <b>or 3,</b> <b>Will <i>NOT</i> Fit Quick</b> <b>Hitch</b>
	CW5000	5000 lbs	290 lbs	<b>SHW 4-Conus 2, 49"</b> <b>(44 usable)</b> <b>Rated at 2697 lbs</b> <b>apiece</b> <b>Other sizes available</b>	<b>No Trailer Mover</b> <b>Option, Fits Cat 2</b> <b>Quick Hitch</b> <b>Compatible,</b> <b>Cat 3 model</b> <b>available</b>