

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

ISLANDIA

TECHNICAL CHARACTERISTICS

Available Formats:	9x35.5		
Style Description:	Wood	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	8
Thickness in mm:	9.8-10.1mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Flat
Rectified:	Yes	Recommended Grout Joint:	2 mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.5% or less	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.42
Scratch Hardness (MOHS)		Breaking Strength:	>1500N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:			

PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	19.59	Pieces per Carton:	9
SqFt per Pallet:	940.32	Pounds per Carton:	
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:	16		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".