

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Patna

TECHNICAL CHARACTERISTICS

Available Formats:	12x24		
Style Description:	Stone	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	
Thickness in mm:	8mm	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Satin
Rectified:	No	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.37
Scratch Hardness (MOHS)	6	Breaking Strength:	>1300
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	5		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.50	Pieces per Carton:	8
SqFt per Pallet:	930.00	Pounds per Carton:	56.42
Boxes per Pallet:	60.00	SqFt per Container:	14880.00
Pallets per Container:	16.00		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".