

TK-5230/5330/5430

7/800 MHz • VHF • UHF

P25 PHASE 1 & 2 • FM ANALOG • LTR



KENWOOD

MAIN FEATURES

- Digital operation in P25 (Phases 1 & 2)
- **P25 Phase 1 Conventional/Trunked Operation (standard)**
- Mixed Digital, FM Analog, and LTR Operation allows intelligent migration in mixed sites and easy migration with digital radios in other sites
- Large, Color 1.74" (240 x 180 pixels) Transflective TFT Display for better interface even in direct sunlight and with use of polarized sunglasses
- Easy to follow GUI for at-a-glance operational status checking and Multi-line Text to convey more information
- 4-way Directional-pad (D-pad) and 2-Position Lever Switch for intuitive control and operation
- Built-In GPS Receiver/Antenna for effective fleet management
- Bluetooth® Module built-in for hands-free operation
- Renowned Audio Quality can be achieved with Active Noise Cancelling that utilizes built-in DSP with two microphones for suppression of ambient noise (dual-mic)
- Built-in 56-bit DES Encryption (4-key DES standard)
- Optional 256-bit AES Encryption
- Built-in Motion Sensor for life-critical man down detection
- microSD/microSDHC Memory Card Slot for increased memory capacity for "Voice & Data"
- IP67/68 and MIL-STD-810 C/D/E/F/G

GENERAL FEATURES

- 6 W (136-174 MHz) Models
- 5 W (380-470, 450-520 MHz) Models
- 3 W (700/800 MHz) Models
- Full Key Models (w/ numeric keypad) and Standard Key Models (w/o numeric keypad)
- Maximum of 4,000 CH/Radio capacity, 512 CH/Zone, 128 Zones
- 1 W Loud Speaker Audio

FM MODES - GENERAL

- Conventional & LTR Zones
- NPSPAC (USA only) Channels (±4.0 Modulation)
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT & Two-Tone
- Built-in Voice Inversion Scrambler

DIGITAL - P25 MODE

- P25 Phase 1 Conventional/Trunked Operation (standard)
- P25 Phase 2 Trunked Operation
- AMBE+2™ Enhanced Vocoder
- Talk Group ID Lists
- Individual ID Lists
- Caller ID Display
- Remote Monitor/Remote Check
- Radio Inhibit
- Encryption Key Zeroize & Retention
- P25 GPS Location
- Over-the-Air Programming*1

INTELLIGENT BATTERY SYSTEM (OPTION)

- System consists of the optional high-capacity Li-Ion Battery Series (KNB-L1/L2/L3), Rapid Charger (KSC-Y32), and Battery Reader (KAS-12) software
- Up to 30 Rapid Chargers can be chain-connected to a PC installed with the KAS-12
- Battery conditions are displayed in color illuminated indicators on the charger, which are also displayed on a connected PC with the same color scheme
- Up to 1,000 batteries can be managed at a time (requires an additional option)

*1 Requires OTAP Management software.



SPECIFICATIONS

Portable Radios

GENERAL		TK-5230	TK-5330	TK-5430
Frequency Range		136-174 MHz	Type 1: 450-520 MHz Type 2: 380-470 MHz	RX: 763-776, 851-870 MHz TX: 763-776, 793-806, 806-825, 851-870 MHz
Max. Channels Per Radio		1024 (Up to 4000 channels with option)		
Number of Zones		128		
Max. Channels Per Zone		512		
Channel Spacing	Analog	12.5/15/20/25*/30* kHz	12.5/25* kHz	12.5/25 kHz
	Digital	6.25/12.5 kHz	6.25/12.5 kHz	12.5 kHz (6.25 kHz)
Power Supply		7.5 V DC ±20%		
Battery Life (5-5-90/10-10-80 duty cycle)	KNB-L1 (2,000 mAh)	10 hours / 6.5 hours		
	KNB-L2 (2,600 mAh)	12.5 hours / 8.5 hours		
	KNB-L3 (3,400 mAh)	17 hours / 11 hours		
Operating Temperature		-22 °F to +140 °F (-30 °C to +60 °C)		
Frequency Stability		±2.0 ppm	±1.0 ppm	±1.5 ppm
Dimensions (W x H x D) Projections Not Included	KNB-L1 (2,000 mAh)	2.28 x 5.47 x 1.52 in. (58 x 139 x 38.8 mm)		
	KNB-L2 (2,600 mAh)	2.28 x 5.47 x 1.65 in. (58 x 139 x 41.8 mm)		
	KNB-L3 (3,400 mAh)	2.28 x 5.47 x 1.86 in. (58 x 139 x 47.2 mm)		
Weight (Dim. & Weight with Battery)	KNB-L1 (2,000 mAh)	15.52 oz (440 g)		
	KNB-L2 (2,600 mAh)	16.57 oz (470 g)		
	KNB-L3 (3,400 mAh)	17.98 oz (510 g)		
RECEIVER		TK-5230	TK-5330	TK-5430
Sensitivity	P25 Digital (5% BER)	0.25 µV		
	P25 Digital (1% BER)	0.40 µV		
	Analog (12 dB SINAD)	0.25 µV		
Selectivity	P25 Digital	60 dB		
	Analog @ 12.5 kHz	67 dB		64 dB
	Analog @ 25 kHz	73 dB		
Intermodulation		73 dB		75 dB
Spurious Rejection		80 dB	75 dB	
Audio Distortion		3%		
Audio Output Power		500 mW/8 Ω (3% Distortion)/1,000 mW/8 Ω (5% Distortion)		
TRANSMITTER		TK-5230	TK-5330	TK-5430
RF Power Output Power		6 to 1 W	5 to 1 W	3 to 1 W
Spurious Emission		-70 dB		
FM Hum & Noise	Analog @ 12.5 kHz	40 dB		
	Analog @ 25 kHz	45 dB		
Audio Distortion		2%		
Emission Designator		16K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 8K10F1W, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D		16K0F3E, 14K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 8K10F1W, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D

MIL STANDARD	810C	810D	810E	810F	810G
Low Pressure	500.1/ I	500.2/ I, II	500.3/ I, II	500.4/ I, II	500.5/ I, II
High Temperature	501.1/ I, II	501.2/ I, II	501.3/ I, II	501.4/ I, II	501.5/ I, II
Low Temperature	502.1/ I	502.2/ I, II	502.3/ I, II	502.4/ I, II	502.5/ I, II
Temp. Shock	503.1/ I	503.2/ I	503.3/ I	503.4/ I, II	503.5/ I
Solar Radiation	505.1/ I	505.2/ I	505.3/ I	505.4/ I	505.5/ I
Rain	506.1/ I, II	506.2/ I, II	506.3/ I, II	506.4/ I, III	506.5/ I, III
Humidity	507.1/ I, II	507.2/ II, III	507.3/ II, III	507.4	507.5/ II
Salt Fog	509.1/ I	509.2/ I	509.3/ I	509.4	509.5
Dust	510.1/ I	510.2/ I	510.3/ I	510.4/ I, III	510.5/ I
Vibration	514.2/ VIII, X	514.3/ I	514.4/ I	514.5/ I	514.6/ I
Shock	516.2/ I, II, V	516.3/ I, IV	516.4/ I, IV	516.5/ I, IV	516.6/ I, IV
Immersion	-	-	-	512.4/ I	512.5/ I

OPTIONAL ACCESSORIES

KNB-L1/L2/L3

Li-ion BATTERY PACK (IP67/68 immersion)



KNB-L1
7.4 V/2000 mAh



KNB-L2
7.4 V/2600 mAh



KNB-L3
7.4 V/3400 mAh

KMC-54WD

SPEAKER MICROPHONE

- 2-mic digital noise cancelling via radio's DSP
- 3.5mm-diameter earphone jack
- Complies with MIL-STD 810C/D/E/F/G
- IP65/67 Dust & Water*

*The earphone jack cap must be closed tightly



KAS-12

BATTERY READER
(PC Software)

KWD-AE30/AE31

SECURE CRYPTOGRAPHIC MODULE

KSC-Y32

RAPID CHARGER



KPG-180AP*

OTAP MANAGER

*Available later

Existing accessories compatible with TK-5230/5330/5430

KSC-32/32S

RAPID CHARGER



KRA-26

VHF HELICAL ANTENNA
(Standard Length)

KSC-326/326S

MULTIPLE CHARGER
(6-unit Rapid Rate)



KRA-27

UHF WHIP ANTENNA
(Standard Length)

KMC-41D

SPEAKER MICROPHONE (IP54/55)



KRA-32

700/800 MHz WHIP ANTENNA

KBH-11

BELT CLIP



KRA-41

VHF STUBBY ANTENNA

KRA-22

VHF HELICAL ANTENNA
(Low Profile)



KRA-42

UHF STUBBY ANTENNA

KRA-23

UHF HELICAL ANTENNA
(Low Profile)




KRA-25

HIGH GAIN VHF ANTENNA
(148-162MHz)

KRA-28

BROAD-BAND VHF ANTENNA (140-170 MHz)




KBH-8DS

BELT LOOP WITH D-RING

KRA-29

BROAD-BAND UHF ANTENNA (380-430 MHz)




KLH-6SW

BELT LOOP WITH D-RING
(Leather Case Back)

KRA-36

700/800 MHz STUBBY ANTENNA



KCT-51

HIROSE 6-PIN ADAPTER

INTERNATIONAL PROTECTION STANDARD

Dust & Water IP54, IP55

Immersion IP67, IP68* *Portable radio immersed for 2 hours at a depth of 1 meter

*25 and 30 kHz are not included in the models sold in the USA or US territories.

Analog measurements made per TIA 603 and specifications shown are typical. Digital measurements made per TIA 102CAA and specifications shown are typical. Details and timing of firmware and software updates are subject to change without notice. Specifications are subject to change without notice.

07.31.15 © Copyright 2015 EFJohnson

The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. SD and microSD are trademarks of SD-3C, LLC in the United States, and/or other countries. AMBE+2™ is a trademark of Digital Voice Systems Inc.

EF Johnson Technologies, Inc.
1440 Corporate Drive, Irving, TX 75038-2401
800.328.3911 • www.efjohnson.com

EFJohnson
TECHNOLOGIES
JVCKENWOOD Group