



9-1/2" OD X 4.000" ID DRILL COLLAR, NON MAG SLICK, AMAGNIT 501, 7-5/8" REG

DRILL COLLAR BODY

Nominal OD (in)	9-1/2
Nominal ID (in)	4.000
Pipe Wall Thickness (in)	2.750
Surface Finish	NON MAG SLICK
Grade	AMAGNIT 501
Cross Sectional Area of Pipe Body (in ²)	58.316
Cross Sectional Area OD (in ²)	70.882
Cross Sectional Area ID (in ²)	12.566
Section Modulus (in ³)	81.527
Polar Section Modulus (in ³)	163.055
Momet of Inertia Drill Collar Body (in ⁴)	387.25
Polar Moment of Inertia Drill Collar Body (in ⁴)	774.51

DRILL COLLAR CONNECTION

Connection	7-5/8" REG
OD (in)	9.500
ID (in)	4.000

DRILL COLLAR ASSEMBLY

Approx Average Length (ft)	31.00
Open End Displacement (gal/ft)	3.03
Closed End Displacement (gal/ft)	3.68
Fluid Capacity (gal/ft)	0.65
Drift Size (in)	3.875

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PETRO PIPE accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.