



PRODUCT DATA SHEETS

SILICONE LUBRICANT SUPER DRY – DRY SILICONE LUBRICANT & MOLD RELEASE

DESCRIPTION

SUPER DRY SILICONE SPRAY reduces friction, stops sticking, squealing and binding of tracks, conveyors, chutes, molds, and sealing equipment. Excellent as a heat stable mold release. Improves slide and glide capabilities on metal and rubber surfaces. **SUPER DRY SILICONE SPRAY** is effective over a wide temperature range -40 degrees F to 285 degrees F. Prevents buildup of glue, lint, oils, and greases on all surfaces.

FEATURES

- **QUICK DRYING**
- **INVISIBLE COATING**
- **FILM IS NOT AFFECTED BY WATER OR OIL**

USE AND DIRECTIONS

- ✚ Clean surface thoroughly before applying
- ✚ Do not thin with any other chemical
- ✚ May be applied by dipping or spraying
- ✚ When spraying, use either airless or compressed air sprayer
- ✚ Apply lightly and evenly
- ✚ Always keep container closed when not in use to prevent evaporation or contamination

ATLANTIC SOLUTIONS, INC
125 N. CHATHAM PARKWAY CHAPEL HILL, NC 27517 Ph:800 476-0895
WWW.ATLANTICSOLUTIONSNC.COM