

LAFAYETTE COUNTY BUILDING DEPARTMENT

P.O. Box 28, Mayo, Florida 32066

RE-ROOFING PERMIT APPLICATION

RESIDENTIAL

COMMERCIAL

MOBILE HOME

JOB ADDRESS: _____

PARCEL NUMBER: _____

Owner: _____ Phone: _____

Owner Address (if different than job site): _____

Contractor: _____ Phone: _____

License Number: _____

Re-Roof Contract value: \$ _____ Value of Structure: \$ _____ Year Built: _____

Square Ft _____ Roof Slope ____/ 12 Existing roof covering _____

Proposed Roof Covering (check all that applicable to this permit)

Asphalt Shingles Metal Panels Flat Roof Mechanically Fastened Tile

Product Approval (covering) FL _____ Product Approval (underlayment) FL _____

Re-Fastening: all sheathing and decking shall be fastened in accordance with either the Florida Existing Building Code (Existing spacing of 8d nails at 6" o.c. requires no additional nails. Any roof sheathing with nails spaced greater than 6" o.c. requires additional nails to create a minimum of 6" o.c. nail spacing. All stapled sheathing requires complete re-nailing. Added nails shall be 2 1/4" 8d ring shank round head) or the roof covering's Miami Dade Product Approval or Florida Product Approval whichever is applicable. (Exception - where re-roofing over existing roofing)

FOR RESIDENTIAL JOBS: Indicate below which method is to be used to satisfy the secondary water barrier requirements:

- The entire roof deck shall be covered with an approved self-adhering polymer modified bitumen sheet. No additional underlayment shall be required on top of this sheet for new installations.
- An asphalt impregnated 30# felt underlayment installed with 1 inch plastic cap or metal cap nails attached to a nail able deck in a grid pattern of 12 inches staggered between overlaps with 6" spacing at the overlaps. Synthetic underlayment shall be fastened in accordance to manufacturer's specifications.

Signed: _____ Date _____