

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

SILK II

TECHNICAL CHARACTERISTICS

Available Formats:	18x32 Matte White Only, 12x24 in Polished & Matte, 12x12 in Polished & Matte, 2x2 Mosaic 12x12 Sheet in Polished & Matte, 3x24 Directional Bullnose in Polished & Matte, 3x12 Cross-cut Bullnose in Polished & Matte		
Style Description:	Fabric	Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Polished & Matte	Number of Faces/Screens:	5
Thickness in mm:	10.2mm-10.3mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte & Polished with Nano Finish/Confirmed Sealed
Rectified:	Cut Edge	Recommended Grout Joint:	No less than 3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< .5%	Static COF:	Wet: .62 - Dry: .74
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF (DCOF):	> .42 (Matte Only)
Scratch Hardness (MOHS)	5	Breaking Strength:	1483N - 1577N
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Grade GA		

PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.56	Pieces per Carton:	7
SqFt per Pallet:	542.40	Pounds per Carton:	55.60 lbs
Boxes per Pallet:	40	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".