

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

POWDER

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 24x24		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Cement	Number of Faces/Screens:	12x24: 32 24x24: 16
Thickness in mm:	9-11mm (size dependent)	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential & Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	16	Surface Type:	Matte, Flat
Rectified:	No	Recommended Grout Joint:	2mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.6
Scratch Hardness (MOHS)	5	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:	Yes/complies w/ISO 10545-13		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes- 12x24*

SqFt per Carton:	11.62	Pieces per Carton:	6
SqFt per Pallet:	464.80	Pounds per Carton:	47.64
Boxes per Pallet:	40	SqFt per Container:	18592
Pallets per Container:			

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".