

Model Name	VI80A-22	
Image Sensor	1/3" CMOS CCD	
Resolution	700TVL	
Picture Elements	PAL: 976(H) x 582(V)	
	NTSC: 976(H) x 494(V)	
CCD/CMOS Sensor	Pixelplus PC3089	
DSP Device	—	
Min. Illumination	0.5 Lux /F2.0	
TV System	PAL/NTSC	
Lens Furnished	Built-in 2.8-12mm Manual Zoom Lens(6-22mm is Optional)	
Infrared Luminary	4 pieces Array IR Leds(Powerful 3 rd generation IR LED)	
Illuminate Distance	100M	
Wavelength	850 nm	
Waterproofin Criterion	IP 66	
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/110,000	
S/N Ratio	More than 48dB	More than 52dB
D-WDR	-	ON / OFF
2DNR	-	OFF/ON
OSD Menu	-	Yes
White Balance	Auto	ATW1 / ATW2 / AWC / MANUAL
Gain Control	Auto	Auto / OFF / LOW / MIDDLE / HIGH
Backlight	-	OFF / BLC / HLC
Gamma	0.45	
Sync. System	Internal	
Video Output	1 Vp-p / 75 Ohms	
Power Supply	DC12V±10%	
Operation Temperature	-10°C~ +50°C RH95% Max	
Dimension	255(L)*152(W)*144(H)mm	
Package Weight	2500g	