

SolarCozi 20W

Solar Powered Attic Vent
Model: GTI/20WA-9ALM

FEATURES

20 Watt Monocrystalline High Efficiency solar panel	Wild life and corrosion resistant screen
Cools up to 1300 sq feet attic space	Leak proof flashing
Aluminum fan blades	Quiet operation and minimal vibration
20 Watt brushless motor with double sealed ball bearings	No electrical set up
Heavy gauge galvanized metal construction is powder coated	Easy installation

SPECIFICATIONS

Shell	32 mils powder coated galvanized Steel
Features	20 W PV panel, 9" Aluminium blade, Thermostat O/F at 86°F±5°F Adjustable PV panel
Motor	12V DC auto inverted brushless motor Aluminium motor shell
Exhaust	1300 CFM
Dim	20.9" X 20.9" X 9.85"
Weight	20 lb



Page:1/4

SolarCozi 20W

WARNING

- Some edges of the solar vent are sharp. Wear safety gloves to avoid injury when handling.
- When cutting or drilling into wall or ceiling, do not damage electrical wiring and other hidden utilities.
- To reduce risk of injury, cover the solar panel with cardboard. The fan operates when the solar panel is exposed to sun light.

RECOMMENDED INSTALLATION INSTRUCTIONS

1. Tools and materials required:

Drill, Pencil, Tape Measure, Sabre Saw, Hammer, Pry Bar, Roofing Cement, Galvanized Roofing Nails.



2. Check your roof orientation and decide the location that has the best sun exposure.


It is recommended south, southwest or west side of the house.



3. Inside your attic find the vent location. Indicate the install place halfway between rafters and drill a guide hole through the roof.




4. At the roof side, with a nail and string, scribe 12" diameter circle on the shingles.



Page:2/4

SolarCozi 20W

- Cut shingles inside of the circle.
 - Drill start hole on inside the 12" circle and cut off roof boards inside of the line.
 - Remove shingle nails around.
 - Apply roofing cement on the bottom side of the vent. Start 2/3 from the top of the square and slide the vent under the shingles.
- Check and align the vent base with the roof hole.
- Lift the shingles and nail or screw the vent base to the roof.
 - Seal shingles and nails with roofing cement.



Page:3/4

SolarCozi 20W

Warranty

GT INDUSTRIAL PRODUCTS COMPANY offers 10 years limited warranty to the owner of the goods.

In case of a return you must present proof of purchase in order to validate your warranty.

GT INDUSTRIAL PRODUCTS COMPANY offers a replacement that will be prorated on the original date of purchase.

GT INDUSTRIAL PRODUCTS COMPANY does not cover any labor, installation, misuse, abuse, improper handling and delivery of the product in the warranty.

If the purchased feels the solar fan is defective in any way, please call or write to GT INDUSTRIAL PRODUCTS COMPANY.

Contact:
GT INDUSTRIAL PRODUCTS COMPANY
600 N 85TH ST SUITE C-101
SEATTLE WA 98103
info@gti-products.com

Page:4/4