Emergency Response Generators -12 KW

To Supply Power for Shelters, Equipment, Air Conditioning, and Lighting

Engine:

Durable Honda GX630 commercial engine Cast iron cylinder sleeves Fuel efficient design EPA and CARB approved Electric start

Generator End:


Clean power at less than 5% total harmonic distortion Steady voltage regulation is safe for sensitive electronics Heavy duty capacitors and diodes 100% copper windings



Features:

Large 15 gallon fuel tank Oversized full power plug Industrial Square D mainline circuit breaker Industry leading 1/60th second reaction time Visi-Trip indicator Made in USA Full commercial warranty - 3 years engine, 2 years generator

Max Power Rating 12000 Cont. Power Rating 10800 Voltage 120/240 Volt 1 PH Cont. Current Rating 90/45 amps Motor Starting Ability (Code G) 5 hp Engine Make/Model Honda GX630 Displacement/Type 688 cc/OHV Cylinder Sleeves Cast Iron Conserv-R Automatic Idle Control N/A Fuel Type Gasoline Starting System Electric Fuel Tank Capacity 15 gal Low Oil Protection Standard Running Time-Full Load 9 hrs **Running Time-Half Load** Hour Meter Included 120 Volt Receptacles 6x20A NEMA 5-20 GFCI 240 Volt Receptacles 1x30A Locking **NEMA L6-30** 120/240 Volt Receptacles 1x60A **NEMA 14-60** Switchless Full Power N/A Dimensions 40x27.5x26.7 in Shipping Weight 460 lbs Warranty (Generator/Engine) 2 yrs/3 vrs DB Rating @ 7 Meters 77 dba **CSA** Approved No **CARB** Approved Yes Country Of Origin USA



PO Box 1531, Auburn, AL 36830 PHONE 334-750-6181 FAX 480-247-4894 DISASTERMEDTECH.COM