

PO Box 1124
One White Oak Trace
Beckley, WV 25801

304.253.0777 phone
304.253.0719 fax

- POWER UTILITY
- HEAVY PROCESS
- MINING
- TUNNELING

SPEC SHEET

DUST EXTRACTORS

Air Handling and Cleaning Systems



PRODUCT RANGE

Model	46	36	33	30	27	24P	18	12
Volume	48,000cfm to 55,000cfm	26,000cfm to 36,000cfm	13,500cfm to 21,250cfm	9,800cfm to 20,250cfm	9,000cfm to 18,000cfm	7,800cfm to 13,800cfm	4,000cfm to 6,800cfm	1,000cfm to 1,550cfm
Motor Size	200 hp	200 hp	75 hp	75 hp	75 hp	60 hp	20 hp	3 hp
Length	163"	138"	130"	83"	77.5"	77.5"	57.2"	44"
Width	76"	60"	40"	40"	37.4"	37.5"	30.5"	16"
Height	85"	77"	51"	51.0"	43.0"	43.5"	25.5"	23.5"
Water Use	13 gpm	11 gpm	8 gpm	8 gpm	7.5 gpm	7 gpm	6 gpm	2 gpm
Weight	±14,200 lbs	±10,500 lbs	±9,800 lbs	±5,000 lbs	±3,900 lbs	±3,400 lbs	±1,350 lbs	±350 lbs

Specifications stated above are for Standard Models. Custom designed systems may vary. Automated control packages are offered as optional features on all Engart Global Systems, U/L and MSHA XP Systems Available.

ADVANTAGES

- Compact High Volume Design.
- Eliminate Explosion Risk Associated with Flammable/Volatile Dust.
- Low Capital, Installation and Operating Cost.
- Unique System to Handle Hydrated Materials Coal or Rock Dust.
- High Dust Collection Efficiencies.
- High Dust Load Capability.
- Can Handle High Temperature or Flammable Gas.
- Flexible Engineering Approach to Optimize Design and Implementation.
- No Reduction in Performance Under High Dust Loads.
- Local Service, Engineering and Support Team.