

### GENERAL INFORMATION

*PROTECTSHUN* is an exclusive formulation that protects interior and exterior surfaces from stains, airborne pollutants, automobile and truck exhausts, red mud, volcanic dust, paint overspray, drywall mud, cement and grout droppings, and other unwanted residues, markings and stains. Encapsulates to keep surfaces from rusting. It is non-toxic, odorless, biodegradable and NON-HAZARDOUS.

*PROTECTSHUN* is effective on natural or painted surfaces, porous and non-porous surfaces, brick, tile, concrete, stucco, wood, E.I.F.S., stone, metals, rebar, granite, split face block, door and window frames, stairway risers and railings, etc. May be used on highway barriers, tunnels, walls, signs, statues, sculptures, stairways, floors.

*PROTECTSHUN* works as a barrier between the unwanted materials and the underlying surface. Washing the surface with water removes unwanted stains. Hot water breaks down the barrier for removal of cement products. Using a power hot water sprayer or PROTECT-OFF and cold water an individual can clean 100 sf of wall surface in about 10 minutes.

### ADVANTAGES

- One Step Application
- Vapor Permeable-allows moisture to escape without damage
- No Thinning or Mixing
- Fast Drying-dries and protects in minutes
- RETARDS THE GROWTH OF MOLD, MILDEW & ALGAE
- NO HAZARDOUS INGREDIENTS
- Estimated Coverage Rate Per Gallon approx. 300-450 sf

### DIRECTIONS FOR USE

*PROTECTSHUN* is best applied with an airless or pump up sprayer on textured surfaces or brush or roller on smooth surfaces.

One gallon covers approximately 300 to 450 sf, depending upon the surface.

*PROTECTSHUN* is easily removed with a hot water spray of 190 degrees F at 300 to 1000 PSI. PROTECT-OFF is an alternative means of removing Protect- Shun when hot water is not available.