

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

COTTO

## TECHNICAL CHARACTERISTICS

Available Formats:	20x20 Available in an indoor/outdoor finish; 3x20 Bullnose available in indoor finish only		
Style Description:	Cotto	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Cotto	Number of Faces/Screens:	N/A
Thickness in mm:	10	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte & Rough Textured
Rectified:	No	Recommended Grout Joint:	No less than 3/16"

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	< .5%	Static COF:	Wet:>0.70    Dry: >0.90
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A
Scratch Hardness (MOHS)	7+	Breaking Strength:	>1300N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	N/A
Chemical Resistance:	N/A		

## PACKING INFORMATION

SqFt per Carton:	13.45	Pieces per Carton:	5
SqFt per Pallet:	484.20	Pounds per SqFt:	5.62 lbs
Boxes per Pallet:	36	SqFt per Container:	N/A
Pallets per Container:	N/A		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".