



## SLOKY Preset Torque Screwdriver—HD Single Sets



The actual packaging may vary



STS-TX-HD

### Description

<b>Product:</b>	SLOKY Preset Torque Screwdriver—HD Single Sets
<b>Models:</b>	STS-TX-HD-06, 07, 08, 09, 10, 15 for TX6, TX7, TX8, TX9, TX10 & TX15
<b>Content:</b>	3 PCS/Set, Single Size 1) 1 PC of HD Handle w/ Adapter 2) 1 PC of 1" Bit for TORX 3) 1 PC of 2" Bit for TORX
<b>Packaging:</b>	Cylinder Twist Top Plastic Container
<b>Dimension:</b>	7 3/4" in Height, 1 1/4" in diameter
<b>Weight:</b>	0.3 lbs

### Specifications

<b>Bits:</b>	High Alloy Steel, Hardness 58°-60°, Color Marked, 1/4" Hex Shank, 1" & 2" (L)
<b>Handle:</b>	Soft Grip HD Handle w/ Adapter, 1 1/4" X 1 1/4" X 4 1/8", (LWH)
<b>Adapters:</b>	Preset Torque, Color Marked, Magnetized, 1/4" Hex Shank, 1 1/2" (L), 1/2" (Dia.)

<b>Preset Torque:</b>	<table border="1"> <tr> <td>TX6</td> <td>■</td> <td>0.6 Nm/5.3 In-lb</td> <td>TX7</td> <td>■</td> <td>0.9 Nm/8.0 In-lb</td> </tr> <tr> <td>TX8</td> <td>■</td> <td>1.2 Nm/10.6 In-lb</td> <td>TX9</td> <td>■</td> <td>1.4 Nm/12.4 In-lb</td> </tr> <tr> <td>TX10</td> <td>■</td> <td>2.0 Nm/17.7 In-lb</td> <td>TX15</td> <td>■</td> <td>3.0 Nm/26.6 In-lb</td> </tr> </table>	TX6	■	0.6 Nm/5.3 In-lb	TX7	■	0.9 Nm/8.0 In-lb	TX8	■	1.2 Nm/10.6 In-lb	TX9	■	1.4 Nm/12.4 In-lb	TX10	■	2.0 Nm/17.7 In-lb	TX15	■	3.0 Nm/26.6 In-lb
TX6	■	0.6 Nm/5.3 In-lb	TX7	■	0.9 Nm/8.0 In-lb														
TX8	■	1.2 Nm/10.6 In-lb	TX9	■	1.4 Nm/12.4 In-lb														
TX10	■	2.0 Nm/17.7 In-lb	TX15	■	3.0 Nm/26.6 In-lb														

<b>Max. Actions:</b>	20,000 Times in Life-Time
<b>Allowance:</b>	±10%
<b>Patents:</b>	US8549963, US201202040734
<b>Applications:</b>	Cutting Tools/Machining, Parts Assembling/Electronics & Aerospace






















## SLOKY Preset Torque Screwdriver

### Features

<b>Replaceable:</b>	All three types of handle are replaceable. Any adapter fits any type of handle
<b>Color Marks:</b>	All the adapters and bits are color marked for easy pairing
<b>Accuracy:</b>	Patented adaptor ensures the preset torque is applied, with the tolerance of $\pm 10\%$
<b>Operation:</b>	Adapter will automatically release the connection with handle when the preset torque is reached and ends the screw tightening operation
<b>Signaling:</b>	Exceeding turns will only generate signal sound, no more torque is applied

### Configuration

 LT Handle	 0.6Nm/5.3 In-lb	 TX/IP 6	
	 0.9Nm/8.0 In-lb	 TX/IP 7	
	 1.2Nm/10.6 In-lb	 TX/IP 8	
	 1.4Nm/12.4 In-lb	 TX/IP 9	
	 2.0Nm/17.7 In-lb	 TX/IP 10	
	 3.0Nm/26.6 In-lb	 TX/IP 15	
	 5.0Nm/44.3 In-lb	 TX/IP 20	
	 5.5Nm/48.7 In-lb	 TX/IP 25	
	 HD Handle		
	 ST Handle		

### Notes

<b>Warning:</b>	Adapters are designed for manual operations, not suitable for use of power tools
<b>Compatibility:</b>	TORX Bits can be used on TORX-PLUS screws, but not vice versa
<b>Trade Mark:</b>	TORX & TORX-PLUS are the registered trademarks of Camcar Textron (USA)