



2900		
TECHNICAL SPECIFICATIONS	Power Source	110V/20A, 220V Option Available
	Cord Length	12 / 3.7M
		5 HP AC Self-Cooling Max Drive
	Incline Motor	1,200 lbs. of thrust
	Speed Sensor	Optical
	Deck	Reversible 1" / 0.8 cm Medium Density Fiberboard
	Reversible Deck	Standard
	Belt	Siegling Multi-Ply with PVC Coating
	Rollers	3.5" / 9 cm w/Sealed Bearings
	Impact System	True Soft System
	Frame Construction	Robotically Welded Heavy-Gauge Steel
	Lubrication	Silax
	Speed Range	0.5 to 12.0 MPH; / 0.8 to 19.3 KMH, / 0.5 to 15.0 MPH; / 0.8 to 24.1 KMH) with Transcend Consoles
	Incline/Decline Range	0% to 18%, (Optional -3% to 18%)
	Quick Access Control	Speed and Incline on Hand Grips with Start and Stop on Quick Access Point
	Handrail Design	Extended Handrails with Molded Rubber, Moisture Resistant Grips
	Contact Heart Rate Monitoring	Yes
	Wireless Heart Rate Monitoring	Polar®
AVAILABLE CONSOLES		Transcend <sup>16</sup> , Transcend <sup>10</sup> , Escalate <sup>15</sup> , Escalate <sup>9</sup> , Emerge
SAFETY	Saftey Clip	Standard
	Extended Handrails	Standard
	Large Straddle Covers	Standard
	User Detection	User Present Detection™
REGULATORY APPROVALS		ETL UL1647, CSA, CE, EN957, FCC
EXTRAS	Accessories	Water Bottle Holder (2), Accessory Tray, Over Molded Reading Rack/Tablet Holder
PHYSICAL SPECIFICATIONS	Footprint	84.5" L x 39.7" W / 214 cm x 100 cm
	Running Surface	63" L x 23" W / 160 cm x 58 cm
	Machine Weight	568 lb / 258 kg
	Shipping Weight	616 lbs / 279 kg
		·
	Maximum User Weight	500 lbs / 226 kg
		500 lbs / 226 kg 11.5" / 29 cm 13.5" / 34 cm with optional decline
WARRANTY	Step-Up Height	11.5" / 29 cm 13.5" / 34 cm with optional decline
WARRANTY	Step-Up Height Portability Warranty Type	11.5" / 29 cm 13.5" / 34 cm with optional decline 2 Front Transport Wheels
WARRANTY	Step-Up Height Portability Warranty Type Frame	11.5" / 29 cm 13.5" / 34 cm with optional decline  2 Front Transport Wheels  Commercial (all dues paying facilities, regardless of usage)
WARRANTY	Step-Up Height Portability Warranty Type Frame Motor	11.5" / 29 cm 13.5" / 34 cm with optional decline 2 Front Transport Wheels Commercial (all dues paying facilities, regardless of usage) Lifetime

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.













