

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

CASTELLO

TECHNICAL CHARACTERISTICS

| | | | |
|---|---|---------------------------|--------------------|
| Available Formats: | 20x20, 13x13, 2x2 Mosaic 13x13 Sheet, 3x13 Bullnose | | |
| Style Description: | Stone-look/Cross-cut | Glaze Application Method: | Rotocolor |
| Visual Characteristics: | Honed Finish | Number of Faces/Screens: | N/A |
| Thickness in mm: | N/A | Number of Punches/Molds: | 1 |
| Modular Suitability: | Yes (Dry lay first) | Body Type: | Porcelain (< .5%) |
| Application: | Residential/Commercial | Color Body Unglazed: | No |
| Recycled Content: Post or Pre Customer | N/A | Surface Type: | Matte |
| Rectified: | No | Recommended Grout Joint: | No less than 3/16" |

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

| | | | |
|------------------------------|-------|--|---------------------|
| Water Absorption: | < .5% | Static COF: | Wet: .60 Dry: 0.60 |
| Shade Variation (1, 2, 3, 4) | V2 | Dynamic COF: | N/A |
| Scratch Hardness (MOHS) | 9 | Breaking Strength: | > 3908 lbs per SqIn |
| Frost Resistant: | Yes | Thermal Shock Resistance: | N/A |
| PEI/Abrasion Resistance: | IV | Deep Abrasion Test <175mm ² : | N/A |
| Chemical Resistance: | N/A | | |

PACKING INFORMATION - 20x20 *Please inquire with Customer Service for additional sizes*

| | | | |
|------------------------|--------|---------------------|-----|
| SqFt per Carton: | 16.27 | Pieces per Carton: | 6 |
| SqFt per Pallet: | 780.96 | Pounds per Carton: | 70 |
| Boxes per Pallet: | 48 | SqFt per Container: | N/A |
| Pallets per Container: | N/A | | |

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".