

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Windsor

TECHNICAL CHARACTERISTICS

Available Formats:	8x48		
Style Description:	Multi Wood Plank	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Wood Look	Number of Faces/Screens:	21
Thickness in mm:	10mm	Number of Punches/Molds:	3
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	≥0.42
Scratch Hardness (MOHS)	MOHS 7	Breaking Strength:	
Frost Resistant:		Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	unaffected		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.72	Pieces per Carton:	6
SqFt per Pallet:	377.28	Pounds per Carton:	
Boxes per Pallet:	24	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".