



6 Geoffrey Road  
 Fairless Hills, PA 19030  
 (215) 295-5800  
 Fax: (215) 295-6100  
 www.TPSAW.com

## TP 2000

**WATER-SOLUBLE SEMI-SYNTHETIC SAWING SOLUTION  
 FORMULATED SPECIFICALLY FOR SAWING**


- Lubricates and cools for extended tool life
- Rejects most tramp oils—hydraulic and oils from materials
- Low to non-foaming
- Long sump life; excellent anti-microbial package prevents rancidity
- Safe to use; non-irritating to the operator
- Can be used in most hard water applications

Item
5 gallon/ 18.9 liter container
55 gallon/ 208.2 liter drum
275 gallon/ 1,040.9 liter tote



### HMIS/WHMIS

Health Index - 1  
 Flammability - 0  
 Reactivity - 0  
 Personal Protection - B



## TP 3000

**WATER-SOLUBLE SYNTHETIC SAWING SOLUTION FORMULATED  
 SPECIFICALLY FOR SAWING**


- Reduces machine wear and improves band saw blade tool life
- Does not contain chlorine, sulfur, silicone, petroleum oils or sulfonates
- Surfaces can be welded or painted over
- Safe to use on metals except magnesium
- Biodegradable

Item
5 gallon/ 18.9 liter container
55 gallon/ 208.2 liter drum
275 gallon/ 1,040.9 liter tote



### HMIS/WHMIS

Health Index - 1  
 Flammability - 0  
 Reactivity - 0  
 Personal Protection - B




## TP 5000

**METAL WORKING LUBRICANT FORMULATED SPECIFICALLY FOR MICRO  
 MANAGEMENT SYSTEMS**

A small amount of this clean lubricant aids in tooth penetration and reduces frictional heat. The result is longer blade life, while maintaining a clean working environment and reducing coolant disposal costs.

- Use when sawing ferrous metals: carbon and alloy steels, tool steels, and stainless steels.

Item
1 gallon/ 3.8 liter container (packed 4 containers per case). No split cases.
55 gallon/ 208.2 liter drum



### HMIS/WHMIS

Health Index - 0  
 Flammability - 1  
 Reactivity - 0  
 Personal Protection - B

