

9-1/2" OD X 3.000" ID DRILL COLLAR, SPIRAL, AISI 4145, 7-5/8" REG

## DRILL COLLAR BODY

Nominal OD (in)	9-1/2
Nominal ID (in)	3.000
Pipe Wall Thickness (in)	3.250
Surface Finish	SPIRAL
Grade	AISI 4145
Cross Sectional Area of Pipe Body (in <sup>2</sup> )	63.814
Cross Sectional Area OD (in <sup>2</sup> )	70.882
Cross Sectional Area ID (in <sup>2</sup> )	7.069
Section Modulus (in <sup>3</sup> )	83.336
Polar Section Modulus (in <sup>3</sup> )	166.671
Momet of Inertia Drill Collar Body (in <sup>4</sup> )	395.84
Polar Moment of Inertia Drill Collar Body (in <sup>4</sup> )	791.69

## DRILL COLLAR CONNECTION

Connection	7-5/8" REG
OD (in)	9.500
ID (in)	3.000

## DRILL COLLAR ASSEMBLY

Approx Average Length (ft)	31.00
Open End Displacement (gal/ft)	3.32
Closed End Displacement (gal/ft)	3.68
Fluid Capacity (gal/ft)	0.37
Drift Size (in)	2.875

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PST Energy Ltd. accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.