



---

**Avionics Integration & Engineering Corporation AG**  
**Rheinfelden, Switzerland**

---

**Part 2**





# THESIS

Comprehensive *Understanding* of the *Essentials* and their accurate *Realization* is the *Key Element* to reach the highest level of *Safety* and *Satisfaction* everywhere.
















































### GULFSTREAM III SAFETY INFORMATION

**SEAT BELTS**  
Move around as much as you like in the cabin while the seat belt sign is off. We suggest, however, that you keep your seat belt fastened while in your seats. Of course, seat belts must be fastened anytime the "FASTEN SEAT BELTS" sign is on.

**SMOKING**  
You may smoke anywhere in the cabin. However, when the "NO SMOKING" sign is on, all smokes must be extinguished. **NO SMOKING WHEN OXYGEN IS IN USE!**

**USE OF OXYGEN MASKS**  
The oxygen masks are located in concealed overhead compartments. These masks will be automatically released to you whenever oxygen is required.  
Should oxygen be required:  
1. Take nearest mask and place over nose and mouth - adjust headband to fit. Do not over tighten as this may reshape mask and cause discomfort.  
2. Check status of the other passengers.  
3. Do not remove your mask until cleared by the crew.

**BREATHE NORMALLY**

A therapeutic oxygen bottle is available in the forward wardrobe compartment in case of need.

**POSITION FOR ABNORMAL LANDING**  
Slow tables and place seatbacks upright. Bend forward and grab ankles.

**LIFE VESTS**  
Life preserver vests are located under each seat.

**ESCAPE WINDOWS**  
4th & 5th windows aft


**EMERGENCY EXIT**  
1. PULL COVER DOWN  
2. PULL HANDLE DOWN  
3. GRASPING RED HANDLES PULL WINDOW INBOARD



**LIFE RAFTS**  
Life rafts are located in the rear of the aircraft under the Lefthand divan. Launching  
1. Remove window exits.  
2. Release tie-down straps securing the rafts.  
3. Tether lines must be secured to the aircraft before removing the raft from the cabin. Use raft tie-down "O" rings.

**"O" Ring**


4. A passenger should be on the wing to receive the raft. Slide raft container out the emergency exit.


**Inflation**  
1. Position container so that it is not directly beside you.  
2. Unstrap covering from triangular handle and pull hard to inflate raft. The raft is ready to board after container opens.  
3. Pull raft close to airplane.  
4. Have passengers walk across wing and tumble into raft, without high-heeled shoes.






















AFC Model

AIEC

Serial Number: 00-000

Part Number: 00-000

Scale: 1:1

NTS A1 (000000) "AFT" PASSENGER SEAT ASSY

Amesbury Engineering & Technology Corporation, 40 Main Street, Suite 101, Amesbury, MA 01753-1011