



## Specifications\*

### Energy Per Blow, Adjustable

Pump Setting 1	49 %	73.7 kNm	54,320 ft.lbs.
Pump Setting 2	66 %	96.0 kNm	70,805 ft.lbs.
Pump Setting 3	83 %	120.7 kNm	89,040 ft.lbs.
Pump Setting 4	100 %	145.5 kNm	107,280 ft.lbs.

Frequency 37 - 52 blows/min

Related Piston Stroke 3.2 - 1.6 m      10.5 - 5.3 ft.

Maximum batter w/o upper cyl. ext. 1:5      -

with upper cylinder extension 1:1      -

Fuel consumption at full load 16.0 L/hr.      4.23 gal./hr.

Oil consumption 1.5 L/hr.      0.39 gal./hr.

### Approx. Weights

Hammer	8888 kg	19,580 lbs.
Piston	4600 kg	10,145 lbs.
Hammer with standard guiding	10025 kg	22,100 lbs.

### Capacities

Fuel Tank	89 L	23.5 gal.
Oil Tank	17 L	4.5 gal.

### Dimensions

A	- Length	5580 mm	18.3 ft.
LH	- Length, standard	6490 mm	21.3 ft.
LH	- Length with hydraulic start	6860 mm	22.5 in.
B	- Center to trip	482 mm	19.0 in.
B1	- Center to trip with cylinder	660 mm	26.0 in.
C	- Center to pump guard	521 mm	20.5 in.
D	- Width of hammer	724 mm	28.5 in.
D1	- Width of trip	940 mm	37.0 in.
W	- Minimum lead width	812 mm	32.0 in.

\*Technical data are subject to change without prior notice

Operating energy based on piston stroke - values are approximate.

Hydraulic start and upper cylinder extension optional.