

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

CROSSCUT CLASSICO

TECHNICAL CHARACTERISTICS

Available Formats:	23x23, 3x23 Bullnose		
Style Description:	Rapolano	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	5
Thickness in mm:	10	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/ Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:		Recommended Grout Joint:	3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	
Scratch Hardness (MOHS)	6	Breaking Strength:	>1300N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Yes		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	18.09	Pieces per Carton:	5
SqFt per Pallet:	578.88	Pounds per Carton:	66.57
Boxes per Pallet:	32	SqFt per Container:	14472.00
Pallets per Container:	25		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".