

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2011

Revised On 01/05/2011

1 Identification of the substance and manufacturer

Trade name: CAST BLAST

Product code: 0000160048

Manufacturer/Supplier: SEYMOUR OF SYCAMORE
917 Crosby Avenue
Sycamore, IL 60178
(815)-895-9101, www.seymourpaint.com

Emergency telephone number: CHEMTEL 1-800-255-3924, 813-248-0585 *if located outside the U.S.*



2 Composition/information on ingredients

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

Chemical Description	Percentage
67-64-1 Acetone	20.51%
74-98-6 propane	18.95%
108-88-3 Toluene	15.54%
106-97-8 n-butane	11.13%
2807-30-9 Glycol Ether EP	5.08%
1330-20-7 xylene (mix)	4.23%

3 Hazards identification

Hazard Information: Extremely flammable liquid and vapor. Keep away from heat, sparks, and flame.
Has narcotizing effect.

Risk phrases: Extremely flammable.
Irritating to eyes.
Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Safety phrases: Keep out of the reach of children.
Keep away from sources of ignition - No smoking.
Do not breathe gas/fumes/vapour/spray.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
Wear suitable protective clothing and gloves.
If swallowed, seek medical advice immediately and show this container or label.
Use only in well-ventilated areas.

Special precautions: Do not spray on a naked flame or any incandescent material.
Buildup of explosive mixtures possible without sufficient ventilation.

Effects of chronic overexposure: May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (0 - 4): Health = 1
Fire = 4
Reactivity = 3

HMS-ratings (0 - 4): Health= 1
Fire= 4
Physical Hazard= 3

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water.

After swallowing: Contact physician or poison control center.

5 Firefighting measures

Extinguishing agents: CO2, sand, extinguishing powder, or water spray.

Special hazards: No further relevant information available.

Protective equipment: No special measures required.

6 Accidental release measures

Personal safety procedures: Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Do not allow product to reach sewage systems or ground water.

Additional precautions: Ensure adequate ventilation.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL 2400 mg/m³, 1000 ppm
REL 590 mg/m³, 250 ppm
TLV Short-term value: 1782 mg/m³, 750 ppm
Long-term value: 1188 mg/m³, 500 ppm
BEI

(Contd. on page 2)
USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2011

Revised On 01/05/2011

Trade name: CAST BLAST

(Contd. of page 1)

74-98-6 propane

PEL 1800 mg/m³, 1000 ppm
 REL 1800 mg/m³, 1000 ppm
 TLV Varies mg/m³, 1000 ppm

108-88-3 Toluene

PEL Short-term value: C 300; 500* ppm
 Long-term value: 200 ppm
 *10-min peak per 8-hr shift
 REL Short-term value: 560 mg/m³, 150 ppm
 Long-term value: 375 mg/m³, 100 ppm
 TLV 75 mg/m³, 20 ppm
 NIC-BEI

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm
 TLV Varies mg/m³, 1000 ppm

1330-20-7 xylene (mix)

PEL 435 mg/m³, 100 ppm
 REL Short-term value: 655 mg/m³, 150 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV Short-term value: 651 mg/m³, 150 ppm
 Long-term value: 434 mg/m³, 100 ppm
 BEI

Hygienic protection:

Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

Odor: Aromatic

pH-value: Not determined.

Boiling point: -44°C (-47°F)

Flash point: -19°C (-2°F)

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol %

Upper Explosion Limit: 10.9 Vol %

Vapor Pressure: 40 PSI, 2750 hPa

Specific Gravity: Between 0.77 and 0.85 (Water equals 1.00)

VOC content: 555.2 g/l / 4.63 lb/gl

VOC content (less exempt solvents): 57.6 %

MIR Value: 1.51

Solids content: 21.9 %

Other information No further relevant information available.

10 Stability and reactivity

Conditions to avoid: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Hazardous reactions: No dangerous reactions known.

Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

Skin effects: No irritant effect.

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), or chlorinated solvents.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

Hazard class: 2.1

Identification number: N/A

Label: 2.1+8

ADR/RID/TDG class: 2 5FC Gases

UN-Number: 1950

(Contd. on page 3)
USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2011

Revised On 01/05/2011

Trade name: CAST BLAST

(Contd. of page 2)

IMDG Class: 2.1
Packaging group: II
EMS Number: F-D,S-U
Marine pollutant: No
ICAO/IATA Class: 2.1
Special marking: Consumer Commodity ORM-D

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene
 1330-20-7 xylene (mix)

TSCA: All ingredients are listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene
 1333-86-4 Carbon black

**California Proposition 65
 chemicals known to cause
 developmental toxicity:
 CANADIAN ENVIRONMENTAL
 PROTECTION ACT:
 WHMIS Symbols for Canada:**

108-88-3 Toluene

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

A - Compressed gas
 D2A - Very toxic material causing other toxic effects
 E - Corrosive material



EPA: A= Known human carcinogen B= Probable human carcinogen
 C= Possible human carcinogen
 D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).
 I: 'Data are inadequate for an assessment of human carcinogeni potential.'
 II: 'Inadequate information to assess carcinogenic potential.'

67-64-1	Acetone	I
108-88-3	Toluene	II
1330-20-7	xylene (mix)	I

IARC: Group 2A: The ingredient is probably carcinogenic to humans.
 Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.
 Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3	Toluene	3
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	3
1330-20-7	xylene (mix)	3

ACGIH: A1-designates a confirmed human carcinogen.
 A2-designates a suspected human carcinogen.
 A3-designates an animal carcinogen.
 A4-designates "not classifiable as a human carcinogen".

67-64-1	Acetone	A4
108-88-3	Toluene	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
1330-20-7	xylene (mix)	A4

NIOSH: The following substances are regulated in the United States with reference to occupational exposure limits:

1333-86-4 Carbon black

Hazard symbols:



Harmful
Extremely flammable

16 Other information

This product was manufactured in the U.S.A.
 The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Abbreviations and acronyms: GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 HMTS: Hazardous Materials Identification System (USA)
 EPA: Environmental Protection Agency
 IARC: International Agency for the Research of Cancer
 NIOSH: National Institute for Occupational Safety and Health
 TSCA: Toxic Substances Control Act
 CPSC: Consumer Product Safety Commission
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 ISO: International Organization for Standardization