

PA5020

DC Wall Mount Power Adapter – 5V 2A

This 5V DC power supply can provide a power source for any electronic device that has a DC5.5x2.5/2.1mm or DC3.5x1.35mm center positive barrel plug and the unit is protected against short-circuit and overload.

ESS PA5020 can be used to power the IP cameras and it is a perfect replacement for the lost or damaged power adapter you have used to power your existing electronics and those other 5VDC devices.



FEATURES

- Input Voltage: 100-240VAC 50/60Hz
- Output Power: 5VDC, 2A
- DC Plug: 5.5 x 2.5/ 2.1mm or 3.5 x 1.35mm
- DC Output Polarity: Centre Positive
- LED Optical Signalization
- Protection: Short-circuit/ Over-voltage/ Over-load

SPECIFICATIONS

Input Voltage	100-240VAC
Frequency	50-60Hz
Output Voltage	DC5V
Output Current	2A
Efficiency	78% Typ.
Ripple & Noise	100mVp-p Typ.
Color	Black, Plastic molded
Application	Indoor
Operation Temperature	0°C to +40°C
Dimensions (L x W x H)	75 x 40 x 38mm
Weight	70g
Length of DC Cable	90cm

ORDERING INFORMATION

PA5020/UK	[ESS] DC Power Adapter 5V 2A, DC plug 5.5x2.5/2.1mm, UK plug
PA5020/US	[ESS] DC Power Adapter 5V 2A, DC plug 5.5x2.5/2.1mm, US plug
PA5020/EU	[ESS] DC Power Adapter 5V 2A, DC plug 5.5x2.5/2.1mm, EU plug
PA5020/UK-3.5x1.35	[ESS] DC Power Adapter 5V 2A, DC plug 3.5x1.35mm, UK plug
PA5020/US-3.5x1.35	[ESS] DC Power Adapter 5V 2A, DC plug 3.5x1.35mm, US plug
PA5020/EU-3.5x1.35	[ESS] DC Power Adapter 5V 2A, DC plug 3.5x1.35mm, EU plug