



www.sealsit.com & www.sealsitoffroad.com

ECONOMY AXLE SEAL 2ND GENERATION (Replaces EAS2-5)

This seal will fit axle tubes with inside diameter between:
2.125 (2 1/8") and 2.250 (2 1/4").

Some of the typical application: Dana 60 - GM 7.5 Metric rear.

PART #	HOUSING I.D.	AXLE SEAL I.D.	FITS AXLE O.D	PASS THRU MAX
EAS25875 FITS	2.125	.875	1.000 / 1"	1.850
	2.250		1 1/16"	
			1 1/8"	
			1 3/16"	
			1.250 / 1 1/4"	
EAS25100 FITS	2.125	1.000	1.300	1.850
	2.250		1 5/16"	
			1 7/16"	
			1 3/8"	
			1.400	
EAS25125 FITS	2.125	1.250	1.500 / 1 1/2"	1.850
	2.250		1.600	
EAS25132 FITS	2.125	1.320	1 5/8"	1.850
	2.250		1.750 / 1 3/4"	

Installation Instructions: Before installing the seal, lightly pack a "low melt" temperature grease inside between the two seals, leaving enough room for the axle to pass through. A coating of about 1/8" to 3/16" is usually sufficient. Applying a bead of orange high temperature silicone around the rubber flange of the seal will help lubricate for installation and to retain the seals location.

DO NOT HIT OR DRIVE SEAL INTO PLACE. THIS COULD RESULT IN CUTTING SEAL ON HOUSING. CALL TECH FOR ASSISTANCE ON INSTALLATION: 860-979-0045



