

KROHNE Variable area (rotameters)

Metal measuring cone



H250 Series

- Accuracy class 1.6%
- SIL 2 compliant
- Totalizer
- 2-wire analog output 4-20mA HART
- Foundation Fieldbus or Profibus PA
- Food & Pharma compliant
- SST indicator housing option



H250 H/U/C/HT Special Series

- Accuracy class 2.5%
- Spring-loaded for horizontal or vertical flow down installation
- Increased measuring range 100:1
- PTFE or ceramic lined options
- High temperatures to 752°F
- High pressures to 43,000 psi



DK32 Series

- Accuracy class 4.0%
- liquids or gas service
- Integrated valve option
- dP regulator valve option



DK37 Series

- Accuracy class 2.5%
- liquid or gas service
- Integrated valve option
- dP regulator option
- 2 optional limit switches or mA analog output

Glass measuring cone



VA40 Series

- Accuracy class 1.0%
- Glass cone protected by metal
- Liquid or gas service
- Food & Pharma compliant
- 2 optional limit switches



VA45 Series

- Accuracy class 2.5%
- Glass cone protected by metal
- Gas service at low pressures
- Food & Pharma compliant



GA24 Series

- Accuracy class 1.0%
- Liquid or gas service
- 2 optional limit switches
- PTFE lined option



DK46,47,48 & 800 Series

- Accuracy 1% to 4%
- Integrated valve option
- dP regulator option