

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

COLISEUM

## TECHNICAL CHARACTERISTICS

Available Formats:	20x20, 12x24, 13x13, 4x13, 3x6, 8x20 Glossy Wall, 1x1 Mosaic 13x13 Sheet, 3x113 Floor Bullnose, 3x8 Glossy Wall Bullnose, Multiple glossy matte wall trims.		
Style Description:	Marble	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Carrara & Calacatta	Number of Faces/Screens:	4x8: 56; Hex: 25
Thickness in mm:	10.5	Number of Punches/Molds:	N/A
Modular Suitability:	Yes (16x16, 8x16, 8x8 Only)	Body Type:	Porcelain (<.5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	Pre-consumer 20%	Surface Type:	Matte/Textured
Rectified:	No	Recommended Grout Joint:	No less than 3/16"

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	< .5%	Static COF:	Wet: 0.60 Dry: 0.70
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	7	Breaking Strength:	>1300N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	Yes		

## PACKING INFORMATION - 4x8 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	7.32	Pieces per Carton:	34
SqFt per Pallet:	572.04	Pounds per Carton:	33.44
Boxes per Pallet:	72	SqFt per Container:	N/A
Pallets per Container:	N/A		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".