

	DUCATI Recommended	Desmo Times Recommended
2 Valve		SNYDER'S Setting
INTAKE		
OPENER	.05 - .12mm (.0019" - .0047")	.1mm (.004")
CLOSER	.03 - .20mm (.001" - .0078")	<.05mm (<.002")
EXHAUST		
OPENER	.05 - .15mm (.0019" - .0059")	.1mm (.004")
CLOSER	.03 - .20mm (.001" - .0078")	<.05mm (<.002")
3 Valve	DUCATI Recommended	SNYDER'S Setting
INTAKE		
OPENER	.10 - .15mm (.004" - .006")	.1mm (.004")
CLOSER	.10 - .15mm (.004" - .006")	.10mm - (.004")
EXHAUST		
OPENER	.10 - .15mm (.004" - .006")	.1mm (.004")
CLOSER	.05 - .10mm (.002" - .004")	.05mm (.002")
4 Valve (pre-testastretta)		
INTAKE	DUCATI Recommended	SNYDER'S Setting
OPENER	.05 - .18mm (.002" - .007")	.1mm (.004")
CLOSER	.15 - .25mm (.006" - .010")	.1mm (.004")
EXHAUST		
OPENER	.05 - .23mm (.002" - .009")	.15mm (.006")
CLOSER	.1 - .2mm (.004" - .008")	.1mm (.004")
Testastretta 4 Valve		
INTAKE & EXHAUST	DUCATI Recommended	SNYDER'S Setting
OPENER	.18 - .23mm (.007" - .009")	.18mm (.007")
CLOSER	.13 - .18mm (.005" - .007")	.13mm (.005")
SPECIAL EDITION DESMOQUATTROS		
	DUCATI Recommended	SNYDER'S Setting
748 R/RS		
INTAKE		
OPENER	.05 - .18mm (.002" - .007")	.1mm (.004")
CLOSER	.15 - .25mm (.006" - .010")	.15mm (.006")
EXHAUST		
OPENER	.05 - .23mm (.002" - .009")	.15mm (.006")
CLOSER	.1 - .2mm (.004" - .008")	.1mm (.004")
916/996 SPS		
INTAKE		
OPENER	.05 - .18mm (.002" - .007")	.1mm (.004")
CLOSER	.15 - .25mm (.006" - .010")	.13mm (.005")
EXHAUST		
OPENER	.05 - .23mm (.002" - .009")	.15mm (.006")
CLOSER	.1 - .2mm (.004" - .008")	.1mm (.004")