

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

**Tampa**

## TECHNICAL CHARACTERISTICS

Available Formats:	18x18, 12x24, 12x12, 3x6, 6x6, 2x2 Mosaic 12x12 Sheet, 3x12 Bullnose		
Style Description:		Glaze Application Method:	
Visual Characteristics:	Rustic Stone	Number of Faces/Screens:	18x18:19, 12x24:15, 12x12:22
Thickness in mm:	10mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential / Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Matte, Textured
Rectified:	No	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.55
Scratch Hardness (MOHS)	8	Breaking Strength:	>1300N
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	GLA, GLH, GA		

## PACKING INFORMATION - 18x18 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.29	Pieces per Carton:	7
SqFt per Pallet:	795.08	Pounds per Carton:	65.75
Boxes per Pallet:	52	SqFt per Container:	10336.04
Pallets per Container:	13		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".