

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME	NATURAL LINEN
-------------	----------------------

TECHNICAL CHARACTERISTICS			
Available Formats:	12x24		
Style Description:	Linen Fabric	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Linen Fabric	Number of Faces/Screens:	1
Thickness in mm:	9.8mm	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain (<.5%)
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Textured
Rectified:	Yes	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	< .5%	Static COF:	N/A
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.45
Scratch Hardness (MOHS)	8	Breaking Strength:	In compliance
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Yes		

PACKING INFORMATION - 12x24 <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	16.57	Pieces per Carton:	9
SqFt per Pallet:	795.36	Pounds per SqFt:	
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:	16		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".