


## HVAC Spiral and Fitting Products




### SPIRAL DUCT

- ✓ Manufactured to the heavier 1985 SMACNA standards
- ✓ Using only G90 coating weight
- ✓ In stock - 3" through 24"
- ✓ Also stock 5 foot lengths of the most popular sizes
- ✓ Tight tolerances ensure consistent and proper fit during installation



### ALUMINUM SPIRAL DUCT

- ✓ Manufactured using 3003 - H14
- ✓ Diameters 4" through 48", and larger sizes also available
- ✓ Tight tolerances ensure consistent and proper fit during installation



### STAINLESS STEEL SPIRAL DUCT

- ✓ Manufactured using 304 or 316 Ti
- ✓ Diameters 4" through 48", and larger sizes also available
- ✓ Tight tolerances ensure consistent and proper fit during installation



### TRUE-FLEX TYPE TFSS - UL – Class 0

- ✓ 304/316Ti Stainless Steel strip, corrugated and formed to desired diameter
- ✓ Mechanically joined using a spike and die
- ✓ Triple seam configuration
- ✓ Temp Range: -40F to +250F and ULC and ULI approved



### SPIN IN COLLARS

- ✓ Manufactured using G90 coating
- ✓ All collars are made with a bead
- ✓ Available from 4" to 20"

#### Configurations available are:

- Without holes
- With holes and damper
- With holes and damper and 2" extension
- With slotted damper and a 2" standoff w/ locking quadrant



### CONICAL SPIN IN COLLARS

- ✓ Manufactured using G90 coating
- ✓ All collars are made with a bead
- ✓ Conical collars provide a superior airflow over the standard collar
- ✓ Available from 4" to 20"

#### Configurations available are:

- Without holes
- With holes and damper
- With holes and damper and 2" extension
- With slotted damper and a 2" standoff w/ locking quadrant



### CONNECTING SLEEVES - TYPE SLD

- ✓ Manufactured using G90 coating
- ✓ All collars are made with a bead on both ends
- ✓ Length 7.5 inches
- ✓ Available from 6" to 12"

#### Configurations available are:

- Without holes
- With slotted damper and a 2" standoff w/ locking quadrant